

# Product data sheet

Specifications



## MGE Galaxy 5500 80kVA 400V Integrated Parallel UPS, Start-up 5x8

G55TUPSM80HS

! Discontinued - Service only

! Discontinued on: Jul 5, 2021

! To be end-of-service on: Dec 31, 2030

### Overview

Presentation	A versatile 3-phase UPS for facility, industrial and data center applications. Configurable system with a comprehensive range of accessories to meet your application demands.
Lead Time	Usually Ships within 2 Weeks

### Main

Main Input Voltage	400 V 3 phases
Other Input Voltage	380 V 415 V
Main Output Voltage	400 V 3 phases
Other Output Voltage	380 V 415 V
Rated Power In W	72000 W
Rated Power In Va	80000 VA
Output Connector Type	Hard wire 4-wire (3P + E) 1
Battery Type	External battery system
Provided Equipment	Installation guide Network management card Start-up service User manual

### Batteries & Runtime

Run Time	<a href="#">View Runtime Graph</a>
Number Of Battery Filled Slots	0
Number Of Battery Free Slots	0
Battery Recharge Time	10 h
Additional Information	Battery runtimes are estimates only. Configurable for 380 : 400 or 415 V 3 Phase nominal output voltage
Battery Voltage	432 V
Battery Power In Vah	0 VAh runtime
Battery Life	8...10 year(s)
Battery Option	G55TBATL7A 1 21500 VAh G55TBATL7B 1 32000 VAh G55TBATL10B 1 40000 VAh G55TBAT2L7C 1 63000 VAh

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Battery Graph Comments	Estimated runtimes based on battery vendor data, at typical environmental conditions, with no electrical input and balanced PF = 0.8 output.
Extended Runtime	0

## General

Bypass Voltage Tolerance	+/- 10 % settable from +/- 4/6/8 and 10 %
Max Bypass Input Current	115 A
Number Of Power Module Free Slots	0
Number Of Power Module Filled Slots	0
Redundant	No

## Physical

Height	190 cm
Width	71.2 cm
Depth	85 cm
Net Weight	520 kg
Mounting Preference	No preference
Usb Compatible	No

## Input

Network Frequency	45...65 Hz
Number Of Input Connectors	1 hard wire 4-wire (3P + E) 1 hard wire 4-wire (3P + N)
Input Voltage Limits	250...470 V adjustable 323...437 V 380 V 340...460 V 400 V 353...477 V 415 V
Maximum Input Current	116 A
Switching Current Capacity	160 A
Max Short Time Withstand Current	30 kA
Input Harmonic Distortion	Less than 3 % for full load
Input Protection Type	3-pole circuit breaker
Inrush Current	200 A peak
Load Power Factor	0.9
Input Power Factor At Full Load	1

## Output

Maximum Configurable Power In W	72000 W
Harmonic Distortion	Less than 2 %
Output Frequency	50/60 Hz +/- 3 Hz user adjustable +/- 0.1 Hz sync to mains 50/60 Hz +/- 1 Hz unsynchronised
Crest Factor	3 : 1
Wave Type	Sine wave
Output Voltage Tolerance	+/- 2% static and 100% load step

Output Harmonic Distortion	< 1% linear load and < 2.5% non-linear load
Output Overload Operation	10 minutes at 125% and 60 seconds at 150%
Required Output Current Protection	63 A
Neutral Output Current	116 A
Bypass Type	Built-in maintenance bypass Built-in static bypass Optional external bypass
Efficiency	93.4 % (full load) 93.1 % (half load)
Maximum Output Current	360 A
Maximum Configurable Power In Va	80000 VA

## Conformance

Product Certifications	CE TÜV VDE
Standards	IEC 62040-1-2 EN/IEC 62040-2 EN/IEC 62040-3 ISO 9001

## Environmental

Ambient Air Temperature For Operation	0...40 °C
Relative Humidity	0...95 %
Operating Altitude	0...3333 ft
Ambient Air Temperature For Storage	-20...45 °C
Storage Relative Humidity	0...95 %
Storage Altitude	0.00...12192.00 m
Acoustic Level	61.4 dBA
Heat Dissipation	16587 Btu/h
Ip Degree Of Protection	IP20

## Communications & Management

Free Slots	2
Preinstalled Device	Network management card 2 with environmental monitoring, out of band access and Modbus
Control Panel	Multifunction LCD status and control console
Emergency Power Off	Yes

## Packing Units

Package 1 Height	203 cm
Package 1 Width	98 cm
Package 1 Length	96 cm
Package 1 Weight	540 kg

## Contractual warranty

Warranty	1 year on-site repair or replace with factory authorized Start-Up, 1 year (parts only)
----------	--

## Sustainability

**Green Premium™ label** label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. **Green Premium** promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low- products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

Eu Rohs Directive

Compliant

[EU RoHS Declaration](#)

---