

Product data sheet

Specifications



MGE Galaxy 5500 20kVA 400-415V Single UPS Marine IP22 RAL 7035, Start-up 5X8

G55TUPU20HMS

! Discontinued

! Discontinued on: Sep 6, 2021

! End-of-service on: Oct 18, 2023

Overview

Presentation	UPS is designed to meet the marine standard requirement.
Lead time	Special Order - Call for Quoted Lead Times

Main

Main Input Voltage	400 V 3 phases
Other Input Voltage	380 V 415 V
Main Output Voltage	400 V 3 phases
Other Output Voltage	380 V 415 V
Rated power in W	18000 W
Rated power in VA	20000 VA
Battery type	External battery system
Provided equipment	Installation guide User manual

Batteries & Runtime

Number of battery filled slots	0
Number of battery free slots	0
Additional information	Configurable for 400 or 415 V 3 Phase nominal output voltage
Battery charger power	5600 W rated
Battery power in VAh	56 VAh runtime
Battery life	8...10 year(s)
Extended runtime	0

General

Bypass wiring configuration	4 wire (3P + N) 5 wire (3P + N + E)
Bypass voltage tolerance	+/- 10 % settable from +/- 4/6/8 and 10 %
Max bypass input current	29 A
Bypass current protection	100 A
Number of power module free slots	0

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Number of power module filled slots	0
Redundant	No

Physical

Colour	Light grey
Height	221 cm
Width	71.2 cm
Depth	85.5 cm
net weight	456 kg
Mounting preference	No preference
USB compatible	No

Input

Network frequency	45...65 Hz
Number of input connectors	1 hard wire 4-wire (3P + E)
Input voltage limits	323...437 V 380 V 340...460 V 400 V 353...477 V 415 V
Maximum input current	42 A
Switching current capacity	125 A
Max short time withstand current	20 kA
Input harmonic distortion	Less than 5 % for full load
Input protection type	GL fuse
Load power factor	0.9
Input Power Factor at Full Load	1

Output

Maximum configurable power in W	18000 W
Harmonic distortion	Less than 2 %
Output frequency	50 Hz programmable +/- 0.5 / 1 / 2 / 4 / 6 / 8 % sync to mains 50 Hz +/- 0.1 % for 50 Hz nominal unsynchronised
Crest factor	3 : 1
Wave type	Sine wave
Output voltage tolerance	+/- 2% static and 100% load step
Output harmonic distortion	< 1% linear load and < 2.5% non-linear load
Output overload operation	10 minutes at 125% and 60 seconds at 150%
Required output current protection	29 A
Neutral output current	43 A
Bypass type	Built-in maintenance bypass Built-in static bypass Optional external bypass
Efficiency	87 % (full load) 80 % (half load)
Maximum output current	190 A

Maximum configurable power in VA	20000 VA
----------------------------------	----------

Conformance

Product certifications	CE TÜV VDE
Standards	EN/IEC 62040-1 EN/IEC 62040-2 EN/IEC 62040-3 IEC 62040-2 ISO 9001

Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 %
Operating altitude	0...3333 ft
Ambient air temperature for storage	-20...45 °C
Storage Relative Humidity	0...95 %
Storage altitude	0.000000000...3657.6 m
Acoustic level	65 dBA
IP degree of protection	IP20 IP32

Communications & Management

Free slots	3
Preinstalled device	Network management card 2 with environmental monitoring, out of band access and Modbus - Schneider
control panel	Multifunction LCD status and control console
Emergency power off	Yes

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	233 cm
Package 1 Width	120 cm
Package 1 Length	108 cm
Package 1 Weight	510 kg

Contractual warranty

Warranty	1 year (parts only), 1 year on-site repair or replace with factory authorized Start-Up
----------	----------------------------------------------------------------------------------------

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)

Eu Rohs Directive

Under investigation
