

# Product data sheet

Specifications



## MGE Galaxy 5500 80kVA 400-415V Single UPS Off Shore IP22 RAL 7035, Start-up 5X8

G55TUPU80HXS

! Discontinued

! Discontinued on: Sep 6, 2021

! End-of-service on: Oct 18, 2023

### Overview

Presentation	UPS is designed to meet the offshore standard requirement.
Lead time	Special Order - Call for Quoted Lead Times

### Main

Main Input Voltage	400 V 3 phases
Other Input Voltage	380 V 415 V
Main Output Voltage	400 V 3 phases
Other Output Voltage	380 V 415 V
Rated power in W	72000 W
Rated power in VA	80000 VA
Battery type	External battery system
Provided equipment	Installation guide User manual

### Batteries & Runtime

Number of battery filled slots	0
Number of battery free slots	0
Additional information	Configurable for 400 or 415 V 3 Phase nominal output voltage
Battery charger power	9300 W rated
Battery power in VAH	93 VAh runtime
Battery life	8...10 year(s)
Extended runtime	0

### General

Bypass wiring configuration	4 wire (3P + N) 5 wire (3P + N + E)
Bypass voltage tolerance	+/- 10 % settable from +/- 4/6/8 and 10 %
Max bypass input current	115 A
Bypass current protection	160 A
Number of power module free slots	0

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Number of power module filled slots	0
Redundant	No

## Physical

Height	218 cm
Width	71.2 cm
Depth	85.5 cm
net weight	556 kg
Mounting preference	No preference
USB compatible	No

## Input

Network frequency	45...65 Hz
Number of input connectors	1 hard wire 4-wire (3P + E) 1 hard wire 4-wire (3P + N)
Input voltage limits	323...437 V 380 V 340...460 V 400 V 353...477 V 415 V
Maximum input current	152 A
Switching current capacity	250 A
Max short time withstand current	20 kA
Input harmonic distortion	Less than 5 % for full load
Input protection type	GL fuse
Load power factor	0.9
Input Power Factor at Full Load	1

## Output

Maximum configurable power in W	72000 W
Harmonic distortion	Less than 2 %
Output frequency	50 Hz programmable +/- 0.5 / 1 / 2 / 4 / 6 / 8 % sync to mains 50 Hz +/- 0.1 % for 50 Hz nominal unsynchronised
Crest factor	3 : 1
Wave type	Sine wave
Output voltage tolerance	+/- 2% static and 100% load step
Output harmonic distortion	< 1% linear load and < 2.5% non-linear load
Output overload operation	10 minutes at 125% and 60 seconds at 150%
Required output current protection	115 A
Neutral output current	115 A
Bypass type	Built-in maintenance bypass Built-in static bypass Optional external bypass
Efficiency	93 % (full load) 90 % (half load)
Maximum output current	240 A

Maximum configurable power in VA	80000 VA
----------------------------------	----------

## Conformance

Product certifications	CE TÜV VDE
Standards	EN/IEC 62040-1 EN/IEC 62040-2 EN/IEC 62040-3 ISO 9001

## Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-20...45 °C
Storage Relative Humidity	0...95 %
Storage altitude	0.0000000000...3657.6 m
Acoustic level	63 dBA
IP degree of protection	IP20 IP32

## Communications & Management

Free slots	3
Preinstalled device	Network management card 2 with environmental monitoring, out of band access and Modbus - Schneider
control panel	Multifunction LCD status and control console
Emergency power off	Yes

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	230 cm
Package 1 Width	120 cm
Package 1 Length	108 cm
Package 1 Weight	580 kg

## Contractual warranty

Warranty	1 year (parts only), 1 year on-site repair or replace with factory authorized Start-Up
----------	--

## Sustainability

**Green Premium™ label** is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)

Eu Rohs Directive

Under investigation

---