

Product datasheet

Specifications



Galaxy VM UPS Modular Battery Cabinet Narrow for 6 battery modules

GVMMODBCN

Overview

| | |
|--------------|--|
| Presentation | Narrow modular battery cabinet with up to a 6 string modular battery capacity. To be used with the GVMMBTU modular battery string. Batteries are not included in the sku and must be purchased separately. |
| Lead Time | Usually Ships within 2 Weeks |

Main

| | |
|--------------------|--------------------|
| Main Input Voltage | 480 V 3 phases |
| Battery Type | VRLA |
| Provided Equipment | Installation guide |

Batteries & Runtime

| | |
|-------------------------------------|--------------------------|
| Battery Location | Battery cabinet |
| Number Of Battery Blocks Per String | 40 |
| Number Of Battery Free Slots | 6 |
| Number Of Battery Filled Slots | 0 |
| Device Mounting | Enclosed battery cabinet |
| Battery Voltage | 480 V |

Physical

| | |
|------------|---------|
| Colour | White |
| Height | 197 cm |
| Width | 37 cm |
| Depth | 85.4 cm |
| Net Weight | 139 kg |

Input

| | |
|-------------------|------------|
| Network Frequency | 40...70 Hz |
|-------------------|------------|

Conformance

| | |
|-----------|--|
| Standards | EN/IEC 62040-3 FCC part 15 class A UL 1778 |
|-----------|--|

Environmental

| | |
|---------------------------------------|-----------|
| Ambient Air Temperature For Operation | 0...40 °C |
|---------------------------------------|-----------|

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

| | |
|-------------------------------------|-------------------|
| Operating Altitude | 0...3333 ft |
| Relative Humidity | 0...95 % |
| Ambient Air Temperature For Storage | -15...40 °C |
| Storage Altitude | 0.00...14999.82 m |
| Storage Relative Humidity | 0...95 % |

Packing Units

| | |
|------------------------------|--------|
| Unit Type Of Package 1 | PCE |
| Number Of Units In Package 1 | 1 |
| Package 1 Height | 215 cm |
| Package 1 Width | 106 cm |
| Package 1 Length | 75 cm |
| Package 1 Weight | 164 kg |

Contractual warranty

| | |
|----------|--------------------------|
| Warranty | 1 year repair or replace |
|----------|--------------------------|

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.


[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Energy Efficient Take-back Transparency

Resource performance

 Energy Efficient Product

 Take-Back Program Available

Well-being performance

 Rohs Exemption Information [Yes](#)

| | |
|-------------------|---------------------------|
| Eu Rohs Directive | Compliant with Exemptions |
|-------------------|---------------------------|

| | |
|-----------------------|---|
| China Rohs Regulation | China RoHS declaration Product out of China RoHS scope. Substance declaration for your information |
|-----------------------|---|

| | |
|--------------------------|---|
| Environmental Disclosure | Product Environmental Profile |
|--------------------------|---|