

# Product data sheet

Specifications



## Galaxy VM 180 kVA Additional UPS for 1+1 480-480 V, 65kAIC, Start up 5x8

GVMRB180KG65S

### Overview

Presentation	Highly compact, energy efficient, redundant 3-phase UPS for data center, facility and industrial applications.
Lead time	Usually Ships within 2 Weeks

### Main

Main Input Voltage	480 V 3 phases
Main Output Voltage	480 V 3 phases
Rated power in W	162 kW
Rated power in VA	180 kVA
Output connector type	Hard wire 4-wire (3P + E) 1 Hard wire 5-wire (3P + N + E) 1
Battery type	External battery system
Provided equipment	Installation guide Start-up service

### Batteries & Runtime

Efficiency	<a href="#">View Efficiency Graph</a>
Number of battery filled slots	0
Number of battery free slots	0
Battery voltage	480 V
Discharge battery voltage	384 V
Maximum short-circuit current	65 kA
Max current discharge	440 A
Battery overload operation	60 seconds at 125% and 30 seconds at 150%
Battery design life	5...10 year(s)
Battery power in VAH	0 VAh runtime
Battery life	7...10 year(s)
Battery graph comments	Estimated runtimes based on battery vendor data, at typical environmental conditions, with no electrical input and balanced PF = 0.9 output.
Extended runtime	0

### General

Bypass voltage tolerance	+/- 10 % settable from +/- 4/6/8 and 10 %
Max bypass input current	217 A

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Bypass current protection	400 A
Redundant	No

## Physical

Colour	White
Height	197 cm
Width	100.2 cm
Depth	85.4 cm
net weight	679.45 kg
USB compatible	No

## Input

Network frequency	40...70 Hz
Number of input connectors	1 hard wire 3-wire (3P + E)
Input voltage limits	360...576 V adjustable 480 V 360...576 V 480 V
Maximum input current	278 A
Switching current capacity	400 A
Max short time withstand current	65 kA
Input harmonic distortion	Less than 3 % for full load
Input protection type	3-pole circuit breaker
Inrush current	200 A peak
Load power factor	0.5 leading to 0.5 lagging
Input Power Factor at Full Load	1

## Output

Maximum configurable power in W	162 kW
Harmonic distortion	Less than 2 %
Output frequency	50/60 Hz +/- 1 Hz sync to mains 50/60 Hz +/- 1 Hz unsynchronised
Crest factor	Unlimited
Wave type	Sine wave
Output voltage tolerance	+/- 1% static and +/- 3% at 100% load step
Output harmonic distortion	< 2% linear load and < 3% non-linear load
Output overload operation	10 minutes at 125% and 60 seconds at 150%
Required output current protection	300 A
Neutral output current	195 A
Bypass type	Built-in static bypass
Efficiency	95.5 % (in battery operation)
Maximum configurable power in VA	180 kVA

## Conformance

Product certifications	cUL listed ENERGY STAR V2.0 (USA) FCC part 15 class A UL 1778
Standards	EN/IEC 62040-3 IBC 2012 and CBC2013 to Sds=2.02g OSHDP

## Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 %
Operating altitude	0...3333 ft
Ambient air temperature for storage	-25...55 °C
Storage Relative Humidity	0...95 %
Storage altitude	0.0000000000...14999.8 m
Acoustic level	65 dBA
heat dissipation	21160 Btu/h
IP degree of protection	IP20

## Communications & Management

Free slots	2
control panel	7" touch screen display
Emergency power off	Optional

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	215.6 cm
Package 1 Width	106 cm
Package 1 Length	149 cm
Package 1 Weight	720.91 kg

## Contractual warranty

Warranty	1 year on-site repair or replace with factory authorized Start-Up
----------	---

## Sustainability

**Green Premium™** label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Energy Efficient   Take-back   Transparency

## Resource performance

✓ Energy Efficient Product

✓ Take-Back Program Available

## Well-being performance

✓ Mercury Free

✓ Rohs Exemption Information   [Yes](#)

## Environmental Certifications

✓ Energy Star®   ENERGY STAR UPS V2.0 (USA)

Eu Rohs Directive   Compliant with Exemptions

Environmental Disclosure   [Product Environmental Profile](#)

Circularity Profile   [End of Life Information](#)

California Proposition 65   WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)