

Product data sheet

Specifications



Galaxy VM 225 kVA Additional UPS for 1+1 480-480 V, 65kAIC, Start up 5x8

GVMRB225KG65S


Overview

Presentation	Highly compact, energy efficient, redundant 3-phase UPS for data center, facility and industrial applications.
Lead time	Usually Ships within 2 Weeks

Main

Main Input Voltage	480 V 3 phase
Main Output Voltage	480 V 3 phase
Kw Rating	202.5 kW
Rated power in VA	225 kVA
Output connector type	Hard Wire 4-wire (3PH + G) 1 Hard Wire 5-wire (3PH + N + G) 1
Battery Type	External battery system
Provided equipment	Dust filter Installation guide Integrated network management Seismic compliance Start-Up Service Top and bottom cable entry

Batteries & Runtime

Efficiency	View Efficiency Graph 
Included Battery Modules	0
Battery Slots Empty	0
Battery Voltage	480V
End of Discharge Battery Voltage	384 V
Maximum short-circuit current	65 kA
End of Discharge Maximum Battery Current	549 A
Overload Operation	60 seconds @ 125% and 30 seconds @ 150%
Battery design life	5...10 year(s)
Battery power in VAh	0 VAh runtime
Battery Life	7...10 year(s)
Battery graph comments	Estimated runtimes based on battery vendor data, at typical environmental conditions, with no electrical input and balanced PF = 0.9 output.
Extendable Run Time	0

General

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Bypass Voltage Tolerance	+/-10% settable from +/-4/6/8 and 10%
Max Bypass Input Current	350 A
Bypass Protection Device	400 A
Redundant	No

Physical

color	White
Height	77.6 in (197 cm)
Width	39.4 in (100.2 cm)
Depth	33.6 in (85.4 cm)
Net Weight	1552.06 lb(US) (704 kg)
USB compatible	No

Input

Input Frequency	40 - 70 Hz
Efficiency at full load	360...576 V adjustable 480 V 360...576 V 480 V
Maximum Input Current per Phase	347 A
Maximum Short Circuit Withstand (Icw)	65 kA
Input Total Harmonic Distortion	Less than 3% for full load
Input protection type	3-pole breaker
Inrush current	200A peak
Load power factor	0.5 leading to 0.5 lagging
Input Power Factor at Full Load	1

Output

Max Configurable Power (Watts)	202.5 kW
Harmonic distortion	Less than 2%
Output Frequency (sync to mains)	50/60 Hz +/- 1 Hz sync to mains 50/60 Hz +/- 1 Hz not synced
Crest factor	Unlimited
Wave type	Sine wave
Output voltage tolerance	+/- 1% static and +/- 3% at 100% load step
Output Voltage THD	< 2% linear load and < 3% non-linear load
Overload Operation	10 minutes @ 125% and 60 seconds @ 150%
Neutral Output Current	244 A
Bypass type	Built-in Static Bypass
Efficiency at full load	95.5 % in battery operation)
Maximum configurable power in VA	225 kVA

Conformance

Product Certifications	cUL Listed ENERGY STAR V2.0 (USA)
------------------------	--------------------------------------

Standards	EN/IEC 62040-3 FCC Part 15 class A IBC 2012 and CBC2013 to Sds=2.02g OSHDP UL 1778
-----------	--

Environmental

Ambient Air Temperature for Operation	32.0000000000...104.0000000000 °F (0...40 °C)
Relative Humidity	0...95 %
Operating altitude	0...3333 ft
Ambient Air Temperature for Storage	-13.0000000000...131.0000000000 °F (-25...55 °C)
Storage Relative Humidity	0...95 %
Storage altitude	0...49212 ft (0.0000000000...14999.8 m)
Acoustic level	65 dBA
heat dissipation	27670 Btu/h
IP degree of protection	IP20

Communications & Management

Free slots	2
control panel	7" touch screen display
Emergency Power Off (EPO)	Optional

Ordering and shipping details

GTIN	731304326533
------	--------------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	84.9 in (215.6 cm)
Package 1 Width	41.7 in (106 cm)
Package 1 Length	58.7 in (149 cm)
Package 1 Weight	1642.4 lb(US) (745 kg)

Contractual warranty

Warranty	1 year on-site repair or replace with factory authorized Start-Up
----------	---

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Energy Efficient Take-back Transparency

Resource performance

✓ Energy Efficient Product

✓ Take-Back Program Available

Well-being performance

✓ Mercury Free

✓ Rohs Exemption Information [Yes](#)

Environmental Certifications

✓ Energy Star® ENERGY STAR UPS V2.0 (USA)

Eu Rohs Directive Compliant with Exemptions

Environmental Disclosure [Product Environmental Profile](#)

Circularity Profile [End of Life Information](#)

California Proposition 65 WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov