

Product data sheet

Specifications



Galaxy VS UPS 15kW 208V for up to 4 internal 9Ah smart modular battery strings, Start-up 5x8

GVSUPS15K0B4FS

Overview

Presentation	Highly efficient, easy-to-deploy 15kW, 208V 3-phase UPS that brings best-in-class power protection and low total cost of ownership to edge, small and medium data centers, as well as to critical infrastructure in commercial and industrial applications. This UPS is for up to 4 smart modular high capacity battery strings, but is supplied without batteries, so you can easily customize the battery runtime. Includes 5x8 start-up service.
Lead Time	Usually Ships within 2 Weeks

Main

Main Input Voltage	208 V 3 phases
Other Input Voltage	200 V 220 V
Main Output Voltage	208 V 3 phases
Other Output Voltage	200 V 220 V
Rated Power In W	15 kW
Rated Power In Va	15 kVA
Battery Type	Internal modular battery VRLA
Provided Equipment	Dust filter Installation manual Integrated network management Start-up service EcoStruxure Ready

Batteries & Runtime

Efficiency	View Efficiency Graph
Battery Voltage	480 V
Discharge Battery Voltage	384 V DC
Max Current Discharge	41 A
Battery Power In Vah	0 VAh runtime
Extended Runtime	0

General

Redundant	No
-----------	----

Physical

Colour	White
--------	-------

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Height	148.5 cm
Width	52.1 cm
Depth	84.7 cm
Net Weight	200 kg
Usb Compatible	No

Input

Network Frequency	40...70 Hz
Input Voltage Limits	177...239 V
Maximum Input Current	54 A
Max Short Time Withstand Current	65 kA
Input Harmonic Distortion	Less than 3 % for full load
Load Power Factor	From 0.7 leading to 0.7 lagging without any derating
Input Power Factor At Full Load	0.99

Output

Maximum Configurable Power In W	15 kW
Harmonic Distortion	Less than 5 %
Output Frequency	50 Hz sync to mains 60 Hz sync to mains
Crest Factor	2.5
Wave Type	Sine wave
Output Voltage Tolerance	+/-1% after 50ms
Output Harmonic Distortion	< 2% linear load and < 5% non-linear load
Output Overload Operation	10 minutes at 125% and 60 seconds at 150%
Bypass Type	Built-in static bypass
Maximum Configurable Power In Va	15 kVA

Conformance

Standards	CSA C22.2 No 107.3 FCC part 15 class A IEC 62040-1-1 IEC 62040-2 IEC 62040-3 UL 1778 5th edition OSHDP
-----------	--

Environmental

Ambient Air Temperature For Operation	0...40 °C
Relative Humidity	0...95 % non-condensing
Operating Altitude	0...3300 ft
Ambient Air Temperature For Storage	-15...40 °C
Storage Relative Humidity	Non-condensing 10...80 %
Storage Altitude	0.00...3048.00 m
Acoustic Level	61 dBA

Heat Dissipation	3059 Btu/h
Ip Degree Of Protection	IP20

Communications & Management

Control Panel	Touch screen LCD user interface
Alarm	Audible and visible alarms prioritized by severity

Packing Units

Package 1 Height	168 cm
Package 1 Width	64 cm
Package 1 Length	99 cm
Package 1 Weight	200 kg

Contractual warranty

Warranty	1 year on-site repair or replace with factory authorized Start-Up
----------	---

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. **Green Premium** promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low- products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)



Energy Efficient Take-back Transparency RoHS/REACH

Resource performance

✓ Energy Efficient Product

✓ Take-Back Program Available

Well-being performance

✓ Mercury Free

✓ Rohs Exemption Information [Yes](#)

Certifications & Standards

Eu Rohs Directive [Compliant](#)
[EU RoHS Declaration](#)

China Rohs Regulation [China RoHS declaration](#)

Environmental Disclosure [Product Environmental Profile](#)

Circularity Profile [End of Life Information](#)