

ISXT110KVM1RSX

NetShelter SX InfraStruXure System Fully Integrated and Assembled with 10kVA Smart UPS RT



❗ Discontinued - Service only

Overview

Presentation	NetShelter® SX single rack InfraStruXure® system that ships factory assembled, wired, and tested - ready to roll into place. A system-level management device provides a single IP address with local and remote monitoring capabilities.
Lead time	Usually Ships within 2 Weeks

General

Provided equipment	Documentation CD User manual Web/SNMP management card
--------------------	---

Physical

Colour	Black
Depth	107 cm
Depth with stable feet	1277.62 mm
Height	199.1 cm
Net weight	289.82 kg
Number of racks	1
Number of rack free space	33
Number of rack unit	42U
Permanent permissible load	1020.58 kg dynamic 1360.78 kg static
Width	60 cm

Input

Network frequency	50/60 Hz +/- 5 Hz auto-sensing
Input voltage limits	160...280 V
Input voltage	208 V
Number of input connectors	1 hard wire 3-wire (2P + E)

Output

Bypass type	Internal bypass (automatic and manual)
Crest factor	3 : 1
Output frequency	50/60 Hz +/- 3 Hz user adjustable +/- 0.1 Hz sync to mains
Output connector type	Hard wire 3-wire (2P + E) 1
Nb of power socket outlets	23 NEMA 5-20R 3 NEMA L5-20R 2 NEMA L6-20R 1 NEMA L6-30R
Output voltage	208 V
PDU type	Metered
Minimum configurable power in W	8000 W
Wave type	Sine wave

Conformance

Product certifications	CUL listed CSA Industry Canada UL listed
Standards	EIA-310D FCC part 15 class A ICES-003 UL 1778 UL 60950

Environmental

Audible noise at 1 meter from surface of unit	55 dBA
Ambient air temperature for operation	0...40 °C
Operating altitude	0...10000 ft
Relative humidity	0...95 %
Ambient air temperature for storage	-15...45 °C
Storage altitude	0.00...15240.00 m
Storage Relative Humidity	0...95 %
Heat dissipation	2216 Btu/h

Batteries & Runtime

Battery charger power	801 W rated 801 W while charging batteries
Battery recharge time	2.2 h
Battery type	Lead-acid battery
Liquid value	0
Number of battery replacement quantity	2.0
Battery power in VAh	1770 VAh

Communications & Management

Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm
Control panel	Multifunction LCD status and control console Network link status LED
Preinstalled device	Network management card with environmental monitoring

Packing Units

Package 1 Weight	303.45 kg
------------------	-----------

Package 1 Height	211.8 cm
Package 1 width	89.9 cm
Package 1 Length	121.9 cm

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------