Product data sheet Characteristics

ISXT11LD1R230V

APC Smart-UPS 1.5kVA, 230V, Low Density Single Rack InfraStruXure® System



Commercial status

Discontinued on: 23 August 2021

ISXT11LD1R230V has not been replaced. Please contact your customer care center for more information.

(!) Discontinued

Overview

Lead time	Usually in Stock	

CD with software	
Rack mounting brackets	
Rack mounting support rails	
Smart UPS signalling RS-232 cable	
User manual	
Web/SNMP management card	
	Rack mounting brackets Rack mounting support rails Smart UPS signalling RS-232 cable User manual

Physical

Overview		
Lead time	Usually in Stock	
General		
	CD with settings	
Provided equipment	CD with software	
	Rack mounting brackets Rack mounting support rails	
	Smart UPS signalling RS-232 cable	
	User manual	
	Web/SNMP management card	
Physical		
Colour	Black	
Depth	107.19 cm	
Height	207.01 cm	
Net weight	191.95 kg	
Number of racks	1	
Number of rack free space	40	
Number of rack unit	42U	
Permanent permissible load	907.18 kg dynamic	
	907.18 kg static	
Width	59.69 cm	
Input		
Network frequency	50/60 Hz +/- 3 Hz auto-sensing	
Input voltage limits	151302 V adjustable	
	160286 V	
Input voltage	230 V	
Plug standard	IEC 60320 C14	
Output		
Rated power in W	0 W	
Crest factor	Up to 5:1	
Sen 4 2021		

Input

Network frequency	50/60 Hz +/- 3 Hz auto-sensing	
Network frequency	30/00 FIZ +/- 3 FIZ auto-sensing	
Input voltage limits	151302 V adjustable	े र
	160286 V	9
Input voltage	230 V	
Plug standard	IEC 60320 C14	

Output

Rated power in W	0 W
Crest factor	Up to 5:1

Output frequency	4753 Hz for 50 Hz nominal sync to mains 5763 Hz for 60 Hz nominal sync to mains
Nb of power socket outlets	4 IEC 60320 C13 2 IEC Jumpers
Output voltage	230 V
Minimum configurable power in W	980 W
Wave type	Sine wave

Conformance

Product certifications	C-Tick CE TÜV VDE	
Standards	EN 50091-1 EN 50091-2	

Environmental

Audible noise at 1 meter from surface of unit	46 dBA
Ambient air temperature for operation	040 °C
Operating altitude	010000 ft
Relative humidity	095 %
Ambient air temperature for storage	-1545 °C
Storage altitude	0.0015240.00 m
Heat dissipation	171 Btu/h

Batteries & Runtime

Battery charger power	144 W rated 144 W while charging batteries
Number of battery free slots	0
Number of battery filled slots	0
Battery recharge time	3 h
Battery type	Lead-acid battery
Liquid value	0
Number of battery replacement quantity	1.0
Battery power in VAh	432 VAh

Communications & Management

Alarm	Alarm when on battery : distinctive low battery alarm : configurable delays
Control panel	LED status display with load and battery bar-graphs and on line : on battery : replace battery : and overload indicators
Free slots	1

Packing Units

D 1 41M 114	0.007.1
Package 1 Weight	213.27 kg

Contractual warranty

	Warranty	2 years repair or replace
--	----------	---------------------------