

Product data sheet

Specifications



APC Line-R 800VA Automatic Voltage Regulator, 3 Universal Outlets, 230V Indonesia

LSW800-IND

Overview

| | |
|-----------|------------------|
| Lead Time | Usually in Stock |
|-----------|------------------|

Main

| | |
|-----------------------|-----------------|
| Main Input Voltage | 230 V |
| Main Output Voltage | 230 V |
| Rated Power In W | 400 W |
| Rated Power In Va | 800 VA |
| Input Connection Type | Schuko CEE 7/7P |
| Cable Length | 1.00 m |
| Provided Equipment | User manual |

Batteries & Runtime

| | |
|--------------------------------|---|
| Number Of Battery Filled Slots | 0 |
| Number Of Battery Free Slots | 0 |

Physical

| | |
|---------------------|--------------------|
| Height | 9.5 cm |
| Width | 18 cm |
| Depth | 11.9 cm |
| Net Weight | 2.03 kg |
| Mounting Preference | No preference |
| Mounting Mode | Not rack-mountable |
| Two Post Mountable | 0 |
| Usb Compatible | No |

Input

| | |
|----------------------|-------------------|
| Network Frequency | 50/60 Hz +/- 5 Hz |
| Input Voltage Limits | 160...285 V |

Output

| | |
|---------------------------------|-------|
| Maximum Configurable Power In W | 400 W |
|---------------------------------|-------|

Conformance

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

| | |
|------------------------|----|
| Product Certifications | CE |
|------------------------|----|

Environmental

| | |
|---------------------------------------|------------------|
| Ambient Air Temperature For Operation | 0...40 °C |
| Relative Humidity | 0...90 % |
| Operating Altitude | 0...3333 ft |
| Ambient Air Temperature For Storage | -20...50 °C |
| Storage Relative Humidity | 0...90 % |
| Storage Altitude | 0.00...1015.90 m |
| Acoustic Level | 40 dBA |

Surge Protection and Filtering

| | |
|-------------------|-------|
| Surge Energy Rate | 148 J |
|-------------------|-------|

Packing Units




| | |
|------------------|----------------|
| Package 1 Height | 9.5 cm |
| Package 1 Width | 457.2 cm |
| Package 1 Length | 11.9 cm |
| Package 1 Weight | 2.03 kg |
| Scc14 | 10731304340949 |

Sustainability

Green Premium™ label is Schneider Electric’s commitment to delivering products with best-in-class environmental performance. **Green Premium** promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low- products. **Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

Well-being performance

| | | |
|---|---|---------------------|
|  | Reach Free Of Svhc | |
|  | Mercury Free | |
|  | Rohs Exemption Information | Yes |
| | | |
| Reach Regulation | REACH Declaration | |
| Eu Rohs Directive | Compliant | EU RoHS Declaration |
| | | |
| China Rohs Regulation | China RoHS declaration | |
| | Pro-active China RoHS declaration (out of China RoHS legal scope) | |