

Product data sheet

Specifications

Rack PDU, Basic, 1U, 15A, 120V, (9)5-15



MO9RM

⚠ Discontinued on: Jun 14, 2022

⚠ Discontinued

Overview

Lead time Usually in Stock

Main

Colour	Beige
product or component type	PDU
PDU type	Basic
Cord length	4.6 m
Number of cables	1
Provided equipment	User manual Rack mounting brackets

Complementary

Input Voltage	120 V
Height	4.44 cm
Width	45.72 cm
Output Voltage	120 V
Depth	14.6 cm
net weight	2.14 kg
mounting location	Front Rear
Mounting preference	No preference
Input Plug Type	NEMA 5-15P
mounting mode	Rack-mounted
Rack units	1U
Mounting position	Horizontal
Permissible voltage	100...125 V
Max line current	15 A
Input current limits	15 A
Load capacity	1800 VA
Number of power socket outlets	9
Network frequency	50/60 Hz

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Outlet type and quantity	9 NEMA 5-15R
--------------------------	--------------

Environment

Product certifications	CSA UL recognized
Standards	UL 1363
Ambient air temperature for operation	0...45 °C
Relative humidity	0...95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-15...65 °C
Storage Relative Humidity	0...95 %
Storage altitude	0.0000000000...15240.0000000000 m

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	6.98 cm
Package 1 Width	47 cm
Package 1 Length	34.3 cm
Package 1 Weight	2.814 kg
SCC14	10731304001598

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------