

APC Essential Surge Protector 10 Outlets, 230V, China standard with USB charging module

P10U-CN

Discontinued on: Jun 14, 2022

(!) Discontinued

Overview

Lead Time Usually in Stock

Main

Main Input Voltage	220 V
Number Of Cables	1
Provided Equipment	USB power adapter

Physical

Height	3.95 cm
Width	5.6 cm
Depth	37.4 cm
Net Weight	0.55 kg
Mounting Preference	No preference
Mounting Mode	Not rack-mountable

Input

Network Frequency	50 Hz
Plug Standard	Australian/Chinese
Maximum Input Current	10 A
Switching Current Capacity	10 A

Output

Outlet Standard	Chinasa autlat
Number Of Power Socket Outlets	11

Conformance

Product Certifications CCC

Environmental

Ambient Air Temperature For Operation	040 °C
Relative Humidity	095 %
Ambient Air Temperature For Storage	-1545 °C

Storage Relative Humidity 0...95 %

Surge Protection and Filtering

Response Time	50 ns common mode
Peak Current	10 kAnormal mode
Surge Energy Rate	600 J

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Scc14	10731304294709

Contractual warranty

Warranty 3 years repair or replace

Sustainability

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency

Well-being performance

Mercury Free	
Rohs Exemption Information	Yes
Eu Rohs Directive	Compliant with Exemptions
Eu Rohs Directive Environmental Disclosure	Compliant with Exemptions Product Environmental Profile