



☐ World Wide [Change](#)

[Home](#)[Product](#)[Support](#)[Service](#)[Selector](#)[How to Buy](#)

SurgeArrest Performance

APC Performance SurgeArrest 11 Outlets with Tel2/Splitter and Coax Jacks, Canada 120V

Complete Surge Protection For High Perform
Computers & Electronics

IncludesCoaxial cable, Cord management s
Telephone Cable, User Manual

P11VT3MP10CN

 [Email Technical Specification](#)

 [Printer Friendly](#)

Technical Specificatio

Product Overvie

Documentatio

Output

Number of Outlets
11
Receptacle Style
NEMA 5-15R

Input

Input Frequency
50/60 Hz
Input Connections
NEMA 5-15P

Cord Length
2.44 meters
Input Breaker Capacity
15A

Surge Protection and Filtering

Surge energy rating
2030 Joules
eP Joule Rating
3400
EMI/RFI Noise rejection (100 kHz to 10 mHz)
70 dB
Dataline protection
RJ11 2-Way Modem/Fax/DSL splitter with protection (four wire dual lines),Cable modem / Video protection
Let Through Voltage Rating
< 40

Physical

Net Weight
1.06 KG
Maximum Height
40.00 mm
Maximum Width
119.00 mm
Maximum depth
302.00 mm
Shipping Weight
1.35 KG
Shipping Height
60.00 mm
Shipping Width
192.00 mm
Shipping Depth
345.00 mm
Master Carton Units
10.00
Master Carton Dimensions (Length x Width x Height)
451 x 363.5 x 389.5 mm
Master Carton Weight
15.10 KG
SCC Codes
1073130425666 0
Color
Black

Environmental

Operating Environment
0 - 45 °C
Operating Relative Humidity
0 - 95%
Operating Elevation
0-3000 meters
Storage Temperature
-15 - 45 °C
Storage Relative Humidity
0 - 95%
Storage Elevation
0-15000 meters

Conformance

Regulatory Approvals
CSA,UL 1363,UL 1449
Standard Warranty
Lifetime
UL 1449 TVSS Rating
330V