

APC Essential SurgeArrest, 3 Outlets, 3 USB Charging Ports, 100-125V

P3U3-JP

! Discontinued on: Jul 3, 2023

① Discontinued

Overview

Lead Time Usually in Stock

Main

Cable Length	2.00 m
Number Of Cables	1
Provided Equipment	User manual

Physical

Colour	White
Height	3.6 cm
Width	13.2 cm
Depth	13.2 cm
Net Weight	0.44 kg
Mounting Preference	No preference
Mounting Mode	Not rack-mountable

Input

Input Power	1500 W
Network Frequency	50/60 Hz
Plug Standard	Japanese 2-pin
Switching Current Capacity	15 A

Output

Number Of Power Socket Outlets	3
Outlet Standard	Japanese 2-pin

Conformance

Product Certifications PSE

Environmental

Ambient Air Temperature For Operation	040 °C
Relative Humidity	090 %

Operating Altitude	03000 ft
Ambient Air Temperature For Storage	-545 °C
Storage Relative Humidity	095 %
Storage Altitude	0.00 4572.00 m

Surge Protection and Filtering

Common Mode Rejection	40 dB
Peak Current	36 kAnormal mode
Surge Energy Rate	540 J

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	7.5 cm
Package 1 Width	15.5 cm
Package 1 Length	14 cm
Package 1 Weight	0.5 kg
Scc14	10731304321818

Contractual warranty

Warranty 2 year (manufacturer's defect)

Apr 6, 2024

Sustainability

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency

Well-being performance

Mercury Free	
Rohs Exemption Information	Yes
Eu Rohs Directive	Compliant with Exemptions
Environmental Disclosure	Product Environmental Profile