

Product data sheet

Specifications

Basic Surge 4 Outlet BS1363 230V



P4-UK

⚠ Discontinued on: Jun 10, 2022

⚠ Discontinued

Overview

Lead time Usually in Stock

Main

Main Input Voltage 230 V

Input Connection Type BS1363A British

Cable length 1.8 m

Number of cables 1

Provided equipment User manual

Physical

Colour Beige

Height 35.56 cm

Width 5.72 cm

Depth 4.14 cm

net weight 0.68 kg

Mounting preference No preference

mounting mode Not rack-mountable

Input

Maximum line current 13 A

Network frequency 50/60 Hz

Output

Number of power socket outlets 4

Outlet standard BS 1363 United Kingdom

Conformance

Product certifications CE

Equipment protection policy Lifetime : 5000 GBP

Environmental

Ambient air temperature for operation 0...40 °C

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Relative humidity	0...95 %
Operating altitude	0...50000 ft
Ambient air temperature for storage	-15...45 °C
Storage Relative Humidity	0...95 %
Storage altitude	0.0000000000...15240.0000000000 m

Surge Protection and Filtering

Response time	0 ns common mode
Common mode rejection	55 dB
Peak current	9 kAcommon mode 4.5 kAnormal mode
Surge energy rate	365 J

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	41.91 cm
Package 1 Width	11.1 cm
Package 1 Length	5.08 cm
Package 1 Weight	0.738 kg
SCC14	10731304019371

Contractual warranty

Warranty	Limited Lifetime (European Union countries only), 3 years (all other countries)
----------	---