

APC Essential Surge Protector 4 Outlets, 230V, non-universal, China

P43-CN

! Discontinued on: Jun 10, 2022

① Discontinued

Overview

Lead Time Usually in Stock

Main

Main Input Voltage 230 V

Number Of Cables 1

Physical

Height	27 cm
Width	4.9 cm
Depth	3.15 cm
Net Weight	0.51 kg
Mounting Preference	No preference
Mounting Mode	Not rack-mountable

Input

Input Power	2200 W
Maximum Line Current	10 A
Network Frequency	50 Hz
Plug Standard	Australian/Chinese
Plug Standard Maximum Input Current	Australian/Chinese 10 A

Output

Number Of Power Socket Outlets	4
Outlet Standard	Chinese outlet

Environmental

Ambient Air Temperature For Operation	040 °C
Relative Humidity	095 %
Ambient Air Temperature For Storage	-1545 °C
Storage Relative Humidity	095 %

Surge Protection and Filtering

Response Time	1 ns common mode
Common Mode Rejection	40 dB
Peak Current	36 kAcommon mode 36 kAnormal mode
Surge Energy Rate	918 J

Packing Units

_	
Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	36.093 cm
Package 1 Width	14.503 cm
Package 1 Length	4.699 cm
Package 1 Weight	0.608 kg
Scc14	10731304284861

Contractual warranty

Warranty 3 years repair or replace

Mar 28, 2024

Sustainability

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency

Well-being performance

Mercury Free	
Rohs Exemption Information	Yes
Eu Rohs Directive	Compliant with Exemptions
Environmental Disclosure	Compliant with Exemptions Product Environmental Profile