

# Product data sheet

Specifications



## APC Essential Surge Protector 4 Outlets, 230V, Universal Sockets with twin USB ports

P4U2-IN

⚠ Discontinued on: Jun 14, 2022

⚠ Discontinued

### Overview

Lead time Usually in Stock

### Main

Cable length 1.5 m

### Physical

Colour White

Height 3.65 cm

Width 6.2 cm

Depth 35 cm

net weight 0.5 kg

Mounting preference No preference

mounting mode Not rack-mountable

### Input

Network frequency 50/60 Hz

plug standard India 3-pin 6A

Switching current capacity 10 A

### Output

Number of power socket outlets 4

outlet standard Universal

### Environmental

Ambient air temperature for operation 0...40 °C

Relative humidity 0...95 %

Operating altitude 0...3000 ft

Ambient air temperature for storage -15...45 °C

Storage Relative Humidity 0...95 %

Storage altitude 0.0000000000...3048.0000000000 m

### Surge Protection and Filtering

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Peak current	6.5 kAcommon mode
Surge energy rate	300 J

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
SCC14	20731304317498

## Contractual warranty

Warranty	Limited Lifetime Warranty
----------	---------------------------

# Sustainability



**Green Premium™ label** is Schneider Electric’s commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product’s sustainability >](#)

## Well-being performance

<div> Mercury Free</div>	
<div><div><div> Rohs Exemption Information</div><div>Yes</div></div></div>	
Eu Rohs Directive	Compliant with Exemptions
Circularity Profile	<a href="#">End of Life Information</a>