Product data sheet

Specifications



APC Essential SurgeArrest 5 outlets with Phone Protection 230V Italy

P5BT-IT

(!) Discontinued

Overview

Lead time Usually in Stock

Main

<u>iviaii i</u>	
Main Input Voltage	230 V
Input Connection Type	CEI 23-16 Italian
Cable length	1.83 m
Number of cables	1
Provided equipment	2 x 1.8 m telephone cables User manual

Oser manual

Physical

Colour	Charcoal
Height	38.5 cm
Width	7 cm
Depth	4.5 cm
Net weight	0.74 kg
Mounting preference	No preference
Mounting mode	Not rack-mountable

Input

Maximum line current	10 A
Network frequency	50/60 Hz

Output

Number of power socket outlets	5
Outlet standard	Italy

Conformance

Product certifications	CE
Equipment protection policy	Lifetime : 50000 euros

Feb 8, 2024 Life Is On Schneider 1

Environmental

Ambient air temperature for operation	040 °C
Relative humidity	095 %
Operating altitude	050000 ft
Ambient air temperature for storage	-1545 °C
Storage Relative Humidity	095 %
Storage altitude	0.0015240.00 m

Surge Protection and Filtering

EP joule rating	1060 J
Response time	0 ns common mode
Common mode rejection	30 dB
Peak current	13 kAcommon mode 13 kAnormal mode
Surge energy rate	960 J

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
SCC14	10731304224058

Offer Sustainability

EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty Limited Lifetime (European Union countries only), 3 years (all other countries)	Warranty	Limited Lifetime (European Union countries only), 3 years (all other countries)
--	----------	---

Recommended replacement(s)