# Disclaimer. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications



# APC Essential SurgeArrest, 6 outlet

### Overview

Lead Time Usually in Stock

# Main

| Main Input Voltage    | 120 V       |  |
|-----------------------|-------------|--|
| Main Output Voltage   | 120 V       |  |
| Rated Power In W      | 0 W         |  |
| Rated Power In Va     | 0 VA        |  |
| Input Connection Type | NEMA 5-15P  |  |
| Cable Length          | 1.83 m      |  |
| Number Of Cables      | 1           |  |
| Provided Equipment    | User manual |  |

# **Batteries & Runtime**

| Number Of Battery Filled Slots | 0 |
|--------------------------------|---|
| Number Of Battery Free Slots   | 0 |

# **Physical**

| Colour              | Charcoal           |  |
|---------------------|--------------------|--|
| Height              | 29.2 cm            |  |
| Width               | 5.7 cm             |  |
| Depth               | 3.8 cm             |  |
| Net Weight          | 0.45 kg            |  |
| Mounting Preference | No preference      |  |
| Mounting Mode       | Not rack-mountable |  |
| Two Post Mountable  | 0                  |  |
| Usb Compatible      | No                 |  |

### Input

Network Frequency 50/60 Hz +/- 5 Hz auto-sensing

### **Output**

Maximum Configurable Power In W

### Conformance

| Product Certifications      | CSA                |
|-----------------------------|--------------------|
| Standards                   | UL 1449            |
| Equipment Protection Policy | Lifetime : \$25000 |

# **Environmental**

| Ambient Air Temperature For Operation | 040 °C         |
|---------------------------------------|----------------|
| Relative Humidity                     | 095 %          |
| Operating Altitude                    | 010000 ft      |
| Ambient Air Temperature For Storage   | -1545 °C       |
| Storage Relative Humidity             | 095 %          |
| Storage Altitude                      | 0.0015240.00 m |

# **Surge Protection and Filtering**

Surge Energy Rate 840 J

# **Packing Units**

| Unit Type Of Package 1       | PCE            |
|------------------------------|----------------|
| Number Of Units In Package 1 | 1              |
| Package 1 Height             | 33.8 cm        |
| Package 1 Width              | 3.8 cm         |
| Package 1 Length             | 14.7 cm        |
| Package 1 Weight             | 0.6 kg         |
| Scc14                        | 10731304211027 |

# **Contractual warranty**

Warranty Limited Lifetime

# **Sustainability**

**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >


Guide to assess a product's sustainability >





Transparency RoHS/REACh

### Well-being performance



### **Certifications & Standards**

| Reach Regulation          | REACh Declaration   |
|---------------------------|---|
| Eu Rohs Directive         | Compliant with Exemptions   |
| Environmental Disclosure  | Product Environmental Profile   |
| Circularity Profile       | End of Life Information   |
| California Proposition 65 | WARNING: This product can expose you to chemicals including: 1,3-Butadiene, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |