# APC Essential SurgeArrest, 7 outlet, phone/DSL line protection, 120V, Latin America

P7T-LM

Discontinued on: 28 September 2021

• End-of-service on: 12 November 2022

## ! Discontinued

#### Overview

Lead time Usually in Stock

#### Main

Main Input Voltage	120 V
Input Connection Type	NEMA 5-15P
Cable length	1.83 m
Number of cables	1
Provided equipment	2 x 1.8 m telephone cables User manual

#### **Physical**

Colour	Charcoal
Height	31.8 cm
Width	7.6 cm
Depth	3.6 cm
Net weight	0.64 kg
Mounting preference	No preference
Mounting mode	Not rack-mountable

### Input

Maximum line current	15 A
Network frequency	50/60 Hz +/- 5 Hz auto-sensing

#### Output

Number of power socket outlets	7
Outlet standard	NEMA 5-15R

#### **Conformance**

UL 1449 TVSS rating	330
Product certifications	CSA

	NOM
Standards	UL 1363 UL 1449
Equipment protection policy	Lifetime: \$25000

### **Environmental**

Ambient air temperature for operation	040 °C
Relative humidity	095 %
Operating altitude	010000 ft
Ambient air temperature for storage	-1545 °C
Storage Relative Humidity	095 %
Storage altitude	0.0015240.00 m

### **Surge Protection and Filtering**

Response time	0 ns common mode
Common mode rejection	20 dB
Peak current	30 kAcommon mode 10 kAnormal mode
Surge energy rate	840 J

# **Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	35.3 cm
Package 1 Width	3.9 cm
Package 1 Length	13.3 cm
Package 1 Weight	0.77 kg
Number of Units in Package 2	12
Package 2 Height	177.80 mm
Package 2 Width	381.00 mm
Package 2 Length	412.75 mm
Package 2 Weight	9.71 kg
Number of Units in Package 3	768
SCC14	10731304255366

# Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile

### **Contractual warranty**

Warranty

Limited Lifetime

Recommended replacement(s)