

Product data sheet

Specifications



Basic Surge 7 Outlet w/Tel 120V

P7T6

⚠ Discontinued on: Jun 10, 2022

⚠ Discontinued

Overview

Lead time Usually in Stock

Main

Main Input Voltage	120 V
Input Connection Type	NEMA 5-15P
Number of cables	1
Provided equipment	2 x 1.8 m telephone cables User manual

Physical

Colour	Beige
Height	3.56 cm
Width	7.62 cm
Depth	31.75 cm
net weight	0.5 kg
Mounting preference	No preference
mounting mode	Not rack-mountable

Input

Maximum line current	15 A
Network frequency	50/60 Hz +/- 5 Hz manual switch

Output

Number of power socket outlets	7
Outlet standard	NEMA 5-15R

Conformance

UL 1449 TVSS rating	330
Product certifications	CSA
Standards	UL 1449
Equipment protection policy	Lifetime : \$25000

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-15...45 °C
Storage Relative Humidity	0...95 %
Storage altitude	0.0000000000...15240.0000000000 m

Surge Protection and Filtering

Data line protected	1-4 RJ11 / 3-6 RJ45
Response time	0 ns common mode
Common mode rejection	55 dB
Peak current	20 kAcommon mode
Surge energy rate	420 J

Packing Units

SCC14	10731304016578
-------	----------------

Contractual warranty

Warranty	Limited Lifetime
----------	------------------