

Product data sheet

Specifications



APC Essential Surge Protector 8 Outlets, 230V, Universal Sockets with twin USB ports

P8U2-IN

⚠ Discontinued on: Jun 14, 2022

⚠ Discontinued

Overview

Lead Time Usually in Stock

Main

Cable Length 1.52 m

Number Of Cables 1

Physical

Colour White

Height 3.65 cm

Width 12 cm

Depth 35 cm

Net Weight 0.69 kg

Mounting Preference No preference

Mounting Mode Not rack-mountable

Input

Network Frequency 50 Hz

Plug Standard India 3-pin 6A

Switching Current Capacity 10 A

Output

Number Of Power Socket Outlets 8

Outlet Standard Deviation Universal

Environmental

Ambient Air Temperature For Operation 0...40 °C

Relative Humidity 0...95 %

Operating Altitude 0...3000 ft

Ambient Air Temperature For Storage -15...45 °C

Storage Relative Humidity 0...95 %

Storage Altitude 0.00...3048.00 m

Surge Protection and Filtering

Peak Current 13 kA common mode

Surge Energy Rate 600 J

Packing Units

Unit Type Of Package 1 PCE

Number Of Units In Package 1 1

Scs14 20731304317528

Contractual warranty

Warranty Limited Lifetime Warranty

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Transparency

Well-being performance

✓ Mercury Free

✓ Rohs Exemption Information [Yes](#)

Eu Rohs Directive [Compliant with Exemptions](#)

Environmental Disclosure [Product Environmental Profile](#)

Circularity Profile [End of Life Information](#)