

> You are here: Home > Products > Stationary Power Distribution Units

Stationary Power Distribution Units

APC 150kVA PDU W/ 480 PRI 208/120 SEC K1 XMER



APC Stationary Power Distribution Units ,
Input: 480V 3PH , Output: 120V, 208V

Includes: User Manual

[More Images](#)

PD150G6FK1

DISCONTINUED : recommended replacement product [PD150G6F](#)

- Email Technical Specifications
- Printer Friendly

- Product Category
- Rack Power Distribution (6)

Row Power Distribution

> Modular Power Distribution

> Modular Power Accessories

> Configurable Power Distribution

> Configurable Power Accessories

> MGE Static Transfer Switches

Room Power Distribution (1)

Transfer Switches (2)

< Return to Power Distribution

Technical Specifications		Documentation	Options
Output			
Nominal Output Voltage	120V,208V		
Input			
Nominal Input Voltage	480V 3PH		
Input Frequency	60 Hz +/- 3 Hz		
Number of Power Cords	1		
Maximum Input Current per phase	180A		
Load Capacity	150 kVA		
Physical			
Net Weight	722.73 KG		
Maximum Height	2070.00 mm		
Maximum Width	914.00 mm		
Maximum Depth	813.00 mm		
Shipping Weight	745.45 KG		
Shipping Height	2235.00 mm		
Shipping Width	1194.00 mm		
Shipping Depth	1168.00 mm		
Color	Black		
Units per Pallet	1.00		
Environmental			
Operating Environment	0 - 40 °C		
Operating Relative Humidity	0 - 95%		
Operating Elevation	0-3000 meters		
Storage Temperature	0 - 45 °C		
Storage Relative Humidity	0 - 95%		
Storage Elevation	0-9000 meters		
Conformance			
Regulatory Approvals	UL 60950		
Standard Warranty	1 year repair or replace,1 year (parts only),optional on-site warranties available		