Stationary Power Distribution Units

APC 225KVA PDU W/ 480 PRI 208/120 SEC K 1 XMER

PD225G6FK1
DISCONTINUED

APC Stationary Power Distribution Units , Input: 480V 3PH , Output: 120V, 208V

Includes: User Manual

Email Technical Specifications
Printer Friendly

More Images

Product Category

- Rack Power Distribution (6)
- Row Power Distribution
  - > Modular Power Distribution
  - > Modular Power Accessories
  - > Configurable Power Distribution
  - > Configurable Power Accessories
  - > MGE Static Transfer Switches
- Room Power Distribution (1)
- Transfer Switches (2)

Return to Power Distribution

Technical Specifications | Documentation

Output	
Nominal Output Voltage	120V,208V

Input	
Nominal Input Voltage	480V 3PH
Input Frequency	60 Hz +/- 3 Hz
Number of Power Cords	1
Maximum Input Current per phase	271A
Load Capacity	225 kVA

Physical	
Net Weight	954.55 KG
Maximum Height	2070.00 mm
Maximum Width	914.00 mm
Maximum Depth	813.00 mm
Shipping Weight	977.27 KG
Shipping Height	2235.00 mm
Shipping Width	1194.00 mm
Shipping Depth	1168.00 mm
Color	Black
Units per Pallet	1.00

Environmental	
Operating Environment	0 - 40 °C
Operating Relative Humidity	0 - 95%
Operating Elevation	0-3000 meters
Storage Temperature	0 - 45 °C
Storage Relative Humidity	0 - 95%
Storage Elevation	0-9000 meters

Conformance	
Regulatory Approvals	UL 60950
Standard Warranty	1 year repair or replace,1 year (parts only),optional on-site warranties available