Stationary Power Distribution Units

APC 300KVA PDU W/ 480PRI 208/120 SEC K1 RATED XMER

APC Stationary Power Distribution Units , Input: 480V 3PH , Output: 120V, 208V

Includes: User Manual

PD300G6FK1
DISCONTINUED

Email Technical Specifications
Printer Friendly

More Images

Technical Specifications | Documentation

Output	
Nominal Output Voltage	120V,208V
Input	
Nominal Input Voltage	480V 3PH
Input Frequency	60 Hz +/- 3 Hz
Number of Power Cords	1
Maximum Input Current per phase	361A
Load Capacity	300 kVA
Physical	
Net Weight	1045.46 KG
Maximum Height	2070.00 mm
Maximum Width	1143.00 mm
Maximum Depth	978.00 mm
Shipping Weight	1068.18 KG
Shipping Height	2235.00 mm
Shipping Width	1372.00 mm
Shipping Depth	1397.00 mm
Color	Black
Units per Pallet	1.00
Environmental	
Operating Environment	0 - 40 °C
Operating Relative Humidity	0 - 95%
Operating Elevation	0-3000 meters
Storage Temperature	0 - 45 °C
Storage Relative Humidity	0 - 95%
Storage Elevation	0-9000 meters
Conformance	
Regulatory Approvals	UL 60950
Standard Warranty	1 year repair or replace,1 year (parts only),optional on-site warranties available