



☐ World Wide [Change](#)

[Home](#)[Products](#)[Support](#)[Services](#)[Selectors](#)[How to Buy](#)

InfraStruXure Power Distribution Units

InfraStruXure® PDU 80kW 400V/400V W/ MBP

Designed to increase flexibility and agility of center power distribution through a design that not require a raised floor.

Includes Installation guide, Service Manual, Manual

Standard Lead Time Usually Ships within 3 Weeks

PD80H5HK1-M

[Contact Sales](#)

[Email Technical Specification](#)

[Printer Friendly](#)

- Technical Specification
- Product Overview
- Documentation
- Options

Output

Nominal Output Voltage
230V,400V 3PH

Input

Nominal Input Voltage
400V 3PH
Number of Power Cords
1
Maximum Input Current per phase
173A
Load Capacity
80 kVA

Physical

Net Weight
954.55 KG
Maximum Height
2070.00 mm
Maximum Width
749.00 mm
Maximum depth
864.00 mm
Shipping Weight
1000.00 KG
Shipping Height
2261.00 mm
Shipping Width
914.00 mm
Shipping Depth
1219.00 mm
Color
Black
Units per Pallet
1.00

Environmental

Operating Environment
0 - 40 °C
Operating Relative Humidity
0 - 95%
Operating Elevation
0-3000 meters
Storage Temperature
-15 - 45 °C
Storage Relative Humidity
0 - 95%
Storage Elevation
0-9000 meters

Conformance

Regulatory Approvals
CE,VDE
Standard Warranty
1 year repair or replace