

APC IT Power Distribution Module 3x1 Pole 3 Wire 20A 240V IEC309 1680cm 1680cm

PDM1320IEC-3P-3

240 V

Installation guide

Overview

Presentation	Factory assembled and tested Power Distribution Modules include circuit breaker, power cord, power connection, and circuit monitoring. Auto-detection of modules by the Modular PDU minimizes installation time.
Lead time	Usually Ships within 3 Weeks
Main	
Main Input Voltage	240 V

Physical

Main Output Voltage

Provided equipment

_		
Colour	Grey	
Height	15.2 cm	
Width	43.2 cm	
Depth	41.9 cm	
net weight	9.09 kg	

Input

Network frequency	60 Hz
Max line current	20 A

Output

Max current draw	20 A
Number of power socket outlets	3 IEC 309 20 A

Conformance

Product certifications UL listed

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	15.2 cm
Package 1 Width	41.9 cm
Package 1 Length	43.2 cm

Package 1 Weight

Contractual warranty

Warranty

1 year repair or replace

10 kg

Sustainability

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >







Take-back Transparency RoHS/REACh

Resource performance



Take-Back Program Available

Well-being performance

Mercury Free



Rohs Exemption Information

Yes

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information