Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

APC IT Power Distribution Module 3 Pole 4 Wire 50A CS50 260cm



PDM3450CS50-260

Overview

Presentation	Factory assembled and tested Power Distribution Modules include circuit breaker, power cord, power connection, and circuit monitoring. Auto-detection of modules by the Modular PDU minimizes installation time.
Lead Time	Usually Ships within 3 Weeks

Main

Main Input Voltage	208 V 3 phases
Main Output Voltage	208 V 3 phases
Output Connector Type	CS50 1
Provided Equipment	Installation guide

Physical

Colour	Black	
Height	12.7 cm	
Width	44.5 cm	
Depth	40.6 cm	
Net Weight	3.91 kg	

Input

Network Frequency	60 Hz
Permissible Voltage	200240 V
Max Line Current	50 A

Output

Max Current Draw	50 A
Number Of Power Socket Outlets	1 CS50

Conformance

Product Certifications UL listed

Packing Units

Package 1 Weight	4.45 kg	
Package 1 Height	12.7 cm	
Package 1 Width	44.5 cm	

Package 1 Length

40.6 cm

Contractual warranty

Warranty

1 year repair or replace

Sustainability

Green Premium[™] label label is Schneider Electric's commitment to delivering products with bestin-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low- products. Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >





Take-back Transparency

Resource performance



Take-Back Program Available

Well-being performance

Mercury Free



Rohs Exemption Information

Reach Regulation	REACh Declaration
Eu Rohs Directive	Under investigation
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information