Specifications



# APC IT Power Distribution Module 3 Pole 4 Wire 50A CS50 560cm

PDM3450CS50-560

Overview	
Presentation	Factory assembled and tested Power Distribution Modules include circuit breaker, power cord, power connection, and circuit monitoring. Auto-detection of modules b the Modular PDU minimizes installation time.
Lead time	Usually Ships within 3 Weeks
Main	
Main Input Voltage	208 V 3 phases
Main Output Voltage	208 V 3 phases
Output connector type	CS50 1
Provided equipment	Installation guide
Physical	
Colour	Black
Height	12.7 cm
Width	44.5 cm
Depth	40.6 cm
net weight	4.82 kg
Input	
Network frequency	60 Hz
Permissible voltage	200240 V
Max line current	50 A
Output	
Max current draw	50 A
Number of power socket outlets	1 CS50
Conformance	
Product certifications	UL listed
Packing Units	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	12.7 cm

Package 1 Width	40.6 cm
Package 1 Length	44.5 cm
Package 1 Weight	5.36 kg

## **Contractual warranty**

Warranty

1 year repair or replace

### Sustainability

**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Take-back Transparency

#### **Resource performance**

Take-Back Program Available

### Well-being performance

Mercury Free

Reach Regulation	REACh Declaration
Eu Rohs Directive	Under investigation
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information