

# Product data sheet

Specifications



## APC IT Power Distribution Module 3 Pole 4 Wire 60A IEC309 320cm

PDM3460IEC309-320

### Overview

|              |                                                                                                                                                                                                                  |
|--------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Presentation | Factory assembled and tested Power Distribution Modules include circuit breaker, power cord, power connection, and circuit monitoring. Auto-detection of modules by the Modular PDU minimizes installation time. |
| Lead time    | Usually Ships within 3 Weeks                                                                                                                                                                                     |

### Main

|                     |                    |
|---------------------|--------------------|
| Main Input Voltage  | 208 V 3 phases     |
| Main Output Voltage | 208 V 3 phases     |
| provided equipment  | Installation guide |

### Physical

|            |         |
|------------|---------|
| Colour     | Black   |
| Height     | 12.7 cm |
| Width      | 44.5 cm |
| Depth      | 40.6 cm |
| net weight | 4.09 kg |

### Input

|                     |             |
|---------------------|-------------|
| Network frequency   | 60 Hz       |
| Permissible voltage | 200...240 V |
| Max line current    | 60 A        |

### Output

|                                |                        |
|--------------------------------|------------------------|
| Max current draw               | 60 A                   |
| Number of power socket outlets | 1 IEC 309 60 A 3P + PE |

### Conformance

|                        |           |
|------------------------|-----------|
| Product certifications | UL listed |
|------------------------|-----------|

### Packing Units

|                              |         |
|------------------------------|---------|
| Unit Type of Package 1       | PCE     |
| Number of Units in Package 1 | 1       |
| Package 1 Height             | 12.7 cm |
| Package 1 Width              | 40.6 cm |

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

|                  |         |
|------------------|---------|
| Package 1 Length | 44.5 cm |
| Package 1 Weight | 4.64 kg |

## Contractual warranty

|          |                          |
|----------|--------------------------|
| Warranty | 1 year repair or replace |
|----------|--------------------------|

# Sustainability

**Green Premium™ label** is Schneider Electric’s commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product’s sustainability >](#)



Take-back   Transparency

## Resource performance

 Take-Back Program Available

## Well-being performance

 Mercury Free

|                          |                                               |
|--------------------------|-----------------------------------------------|
| Reach Regulation         | <a href="#">REACH Declaration</a>             |
| Eu Rohs Directive        | Under investigation                           |
| Environmental Disclosure | <a href="#">Product Environmental Profile</a> |
| Circularity Profile      | <a href="#">End of Life Information</a>       |