

Product data sheet

Specifications



APC IT Power Distribution Module 3 Pole 4 Wire 60A IEC309 500cm

PDM3460IEC309-500

Overview

Presentation	Factory assembled and tested Power Distribution Modules include circuit breaker, power cord, power connection, and circuit monitoring. Auto-detection of modules by the Modular PDU minimizes installation time.
Lead Time	Usually Ships within 3 Weeks

Main

Main Input Voltage	208 V 3 phases
Main Output Voltage	208 V 3 phases
Provided Equipment	Installation guide

Physical

Colour	Black
Height	12.7 cm
Width	44.5 cm
Depth	40.6 cm
Net Weight	4.64 kg

Input

Network Frequency	60 Hz
Permissible Voltage	200...240 V
Max Line Current	60 A

Output

Max Current Draw	60 A
Number Of Power Socket Outlets	1 IEC 309 60 A 3P + PE

Conformance

Product Certifications	UL listed
------------------------	-----------

Packing Units

Package 1 Height	12.7 cm
Package 1 Width	44.5 cm
Package 1 Length	40.6 cm
Package 1 Weight	5.18 kg

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Contractual warranty

Warranty	1 year repair or replace
----------	--------------------------

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. **Green Premium** promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low- products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)



Take-back Transparency

Resource performance

✓ Take-Back Program Available

Well-being performance

✓ Mercury Free

✓ Rohs Exemption Information [Yes](#)

Eu Rohs Directive Under investigation

Environmental Disclosure [Product Environmental Profile](#)

Circularity Profile [End of Life Information](#)