

APC IT Power Distribution Module 3 Pole 5 Wire 20A 240V IEC309 260cm

PDM3520IEC309-260

Overview

Presentation	Factory assembled and tested Power Distribution Modules include circuit breaker, power cord, power connection, and circuit monitoring. Auto-detection of modules by the Modular PDU minimizes installation time.
Lead time	Usually Ships within 3 Weeks

Main

Main Input Voltage	230 V
Main Output Voltage	240 V
Input Connection Type	IEC 60309
Provided equipment	Installation quide

Physical

Colour	Grey	
Height	12.7 cm	
Width	44.5 cm	
Depth	40.6 cm	
net weight	3.91 kg	

Input

Network frequency	60 Hz
Permissible voltage	200240 V
Max line current	20 A

Output

Max current draw	20 A
Number of power socket outlets	1 IEC 309

Conformance

Product certifications UL listed

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	12.7 cm

Package 1 Width	40.6 cm	
Package 1 Length	44.5 cm	
Package 1 Weight	4.45 kg	

Contractual warranty

Warranty 1 year repair or replace

Sustainability

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Take-back Transparency

Resource performance



Take-Back Program Available

Well-being performance



Mercury Free

Reach Regulation	REACh Declaration
Eu Rohs Directive	Under investigation
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information