

# APC IT Power Distribution Module 3 Pole 5 Wire 20A 240V IEC309 560cm

PDM3520IEC309-560

#### **Overview**

Presentation	Factory assembled and tested Power Distribution Modules include circuit breaker, power cord, power connection, and circuit monitoring. Auto-detection of modules by the Modular PDU minimizes installation time.
Lead time	Usually Ships within 3 Weeks

#### Main

Main Input Voltage	230 V
Main Output Voltage	240 V
Input Connection Type	IEC 60309
provided equipment	Installation guide

# **Physical**

Colour	Grey
Height	12.7 cm
Width	44.4 cm
Depth	40.6 cm
net weight	4.82 kg

# Input

Network frequency	60 Hz
Permissible voltage	200240 V
Max line current	20 A

### **Output**

Max current draw	20 A
Number of power socket outlets	1 IEC 309

#### **Conformance**

Product certifications UL listed

# **Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	12.7 cm

Package 1 Width	40.6 cm
Package 1 Length	44.4 cm
Package 1 Weight	5.36 ka

# **Contractual warranty**

Warranty 1 year repair or replace

### Sustainability

**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Take-back Transparency

#### Resource performance



Take-Back Program Available

### Well-being performance



Mercury Free

Reach Regulation	REACh Declaration
Eu Rohs Directive	Under investigation
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information