Specifications



## APC IT Power Distribution Module 3 Pole 5 Wire 20A 240V IEC309 740cm

PDM3520IEC309-740

Presentation	Factory assembled and tested Power Distribution Modules include circuit breaker, power cord, power connection, and circuit monitoring. Auto-detection of modules by the Modular PDU minimizes installation time.	
Lead time	Usually Ships within 3 Weeks	
Main		
Main Input Voltage	230 V	
Main Output Voltage	240 V	
Input Connection Type	IEC 60309	
Provided equipment	Installation guide	
Physical		
Colour	Grey	
Height	12.7 cm	
Width	44.4 cm	
Depth	40.6 cm	
net weight	5.36 kg	
Input		
Network frequency	60 Hz	
Permissible voltage	200240 V	
Max line current	20 A	
Output		
Max current draw	20 A	
Number of power socket outlets	1 IEC 309	
Conformance		
Product certifications	UL listed	
Packing Units		
Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	12.7 cm	

Package 1 Width	40.6 cm
Package 1 Length	44.4 cm
Package 1 Weight	5.91 kg

# **Contractual warranty**

Warranty

1 year repair or replace

### Sustainability

**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Take-back Transparency

#### **Resource performance**

Take-Back Program Available

### Well-being performance

Mercury Free

Reach Regulation	REACh Declaration
Eu Rohs Directive	Under investigation
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information