

Product data sheet

Specifications

APC IT Power Distribution Module 3 Pole 5 Wire 20A L21-20 1040cm



PDM3520L2120-1040

Overview

Presentation	Factory assembled and tested Power Distribution Modules include circuit breaker, power cord, power connection, and circuit monitoring. Auto-detection of modules by the Modular PDU minimizes installation time.
Lead Time	Usually in Stock

Main

Main Input Voltage	208 V 3 phases
Main Output Voltage	120 V
Provided Equipment	Installation guide

Physical

Colour	Black
Height	12.7 cm
Width	44.5 cm
Depth	40.6 cm
Net Weight	4.29 kg

Input

Network Frequency	60 Hz
Permissible Voltage	200...240 V
Max Line Current	20 A

Output

Max Current Draw	20 A
Number Of Power Socket Outlets	1 NEMA L21-20

Conformance

Product Certifications	UL listed
------------------------	-----------

Packing Units

Package 1 Weight	5.2 kg
Package 1 Height	12.7 cm
Package 1 Width	44.5 cm
Package 1 Length	40.6 cm

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. **Green Premium** promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low- products. **Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)



Take-back Transparency

Resource performance

 Take-Back Program Available

Well-being performance

 Mercury Free

 Rohs Exemption Information [Yes](#)

Reach Regulation [REACH Declaration](#)

Eu Rohs Directive Under investigation

Environmental Disclosure [Product Environmental Profile](#)

Circularity Profile [End of Life Information](#)