Specifications

# 

PDM3520L2120-560

APC IT Power Distribution Module 3

Pole 5 Wire 20A L21-20 560cm

Presentation	Factory assembled and tested Power Distribution Modules include circuit breaker, power cord, power connection, and circuit monitoring. Auto-detection of modules by the Modular PDU minimizes installation time.	
Lead time	Usually Ships within 3 Weeks	
Main		
Main Input Voltage	208 V 3 phases	
Main Output Voltage	120 V	
Provided equipment	Installation guide	
Physical		
Colour	Black	
Height	12.7 cm	
Width	44.5 cm	
Depth	40.6 cm	
net weight	4.82 kg	
Input		
Network frequency	60 Hz	
Permissible voltage	200240 V	
Max line current	20 A	
Output		
Max current draw	20 A	
Number of power socket outlets	1 NEMA L21-20	
Conformance		
Product certifications	UL listed	
Packing Units		
Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	12.7 cm	

Package 1 Width

40.6 cm

Package 1 Length	44.5 cm	
Package 1 Weight	5.36 kg	

## **Contractual warranty**

Warranty

1 year repair or replace

### Sustainability

**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Take-back Transparency

#### **Resource performance**

Take-Back Program Available

#### Well-being performance

Mercury Free

Reach Regulation	REACh Declaration
Eu Rohs Directive	Under investigation
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information