Specifications

APC IT Power Distribution Module 3 Pole 5 Wire 30A L21-30 980cm



PDM3530L2130-980

Overview	
Presentation	Factory assembled and tested Power Distribution Modules include circuit breaker, power cord, power connection, and circuit monitoring. Auto-detection of modules by the Modular PDU minimizes installation time.
Lead time	Usually Ships within 3 Weeks
Main	
Main Input Voltage	208 V 3 phases
Main Output Voltage	120 V
provided equipment	Installation guide
Physical	
Colour	Black
Height	12.7 cm
Width	44.5 cm
Depth	40.6 cm
net weight	6.09 kg
Input	
Network frequency	60 Hz
Permissible voltage	200240 V
Max line current	30 A
Output	
Max current draw	30 A
Number of power socket outlets	1 NEMA L21-30
Conformance	
Product certifications	UL listed
Packing Units	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	12.7 cm
Package 1 Width	40.6 cm

Package 1 Length	44.5 cm
Package 1 Weight	6.64 kg

Contractual warranty

Warranty

1 year repair or replace

Sustainability

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Take-back Transparency

Resource performance

Take-Back Program Available

Well-being performance

Mercury Free

Reach Regulation	REACh Declaration
Eu Rohs Directive	Under investigation
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information