Specifications



APC IT Power Distribution Module 3 Pole 5 Wire 32A IEC309 260cm

PDM3532IEC-260

Overview	
Presentation	Factory assembled and tested Power Distribution Modules include circuit breaker, power cord, power connection, and circuit monitoring. Auto-detection of modules by the Modular PDU minimizes installation time.
Lead time	Usually Ships within 3 Weeks
Main	
Main Input Voltage	400 V 3 phases
Main Output Voltage	230 V 400 V 3 phases
Provided equipment	Installation guide
Physical	
Colour	Grey
Height	15.2 cm
Width	43.2 cm
Depth	40.6 cm
net weight	2.39 kg
Input	
Network frequency	50 Hz
Max line current	32 A
Output	
Max current draw	32 A
Number of power socket outlets	1 IEC 309 32 A
Conformance	
Product certifications	CE VDE
Packing Units	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	15.2 cm

Package 1 Width

40.6 cm

Package 1 Length	43.2 cm	
Package 1 Weight	3.3 kg	

Contractual warranty

Warranty

1 year repair or replace

Sustainability

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

EQ

Guide to assess a product's sustainability >



()

Take-back Transparency RoHS/REACh

Resource performance

Take-Back Program Available

Well-being performance

Mercury Free

Rohs Exemption Information

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information

Yes