

Product data sheet

Specifications



APC Modular Remote Power Panel, 144kVA, 400A, 208V, 72 Pole, 300mm

PDPM144F

Overview

Presentation	A fully scalable power distribution system that cost-effectively provides high levels of availability and enables the quick addition of circuits and cord-sets.
Lead Time	Usually Ships within 3 Weeks

Main

Main Input Voltage	208 V 3 phases
Main Output Voltage	208 V 3 phases
Provided Equipment	Installation guide

Physical

Height	200.2 cm
Width	30 cm
Depth	107.7 cm
Net Weight	160 kg
Mounting Location	Front
Mounting Preference	No preference
Mounting Mode	Not rack-mountable

Input

Network Frequency	60 Hz
Permissible Voltage	200...240 V
Max Line Current	400 A

Output

Max Current Draw	400 A
------------------	-------

Conformance

Product Certifications	UL listed
Standards	OSHPD

Packing Units

Package 1 Weight	182.27 kg
Package 1 Height	224.8 cm

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Package 1 Width	85.1 cm
Package 1 Length	120.6 cm

Contractual warranty

Warranty	1 year repair or replace
----------	--------------------------

Sustainability

Green Premium™ label label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. **Green Premium** promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low- products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

Eu Rohs Directive

Pro-active compliance (Product out of EU RoHS legal scope)

[EU RoHS Declaration](#)
