

Product data sheet

Specifications



APC 150kVA Modular PDU Bottom Feed Side Car, 300mm

PDPM150SC

Overview

| | |
|-----------|------------------------------|
| Lead Time | Usually Ships within 3 Weeks |
|-----------|------------------------------|

Main

| | |
|---------------------|---|
| Main Input Voltage | 208 V 208 V 3 phases 480 V 3 phases 600 V 3 phases |
| Main Output Voltage | 208 V 208 V 3 phases 415 V 3 phases 480 V 3 phases 600 V 3 phases |
| Provided Equipment | Installation guide |

Physical

| | |
|---------------------|--------------------|
| Colour | Black |
| Height | 200.4 cm |
| Width | 30 cm |
| Depth | 107 cm |
| Net Weight | 134 kg |
| Mounting Preference | No preference |
| Mounting Mode | Not rack-mountable |

Input

| | |
|----------------------------|---------------------------------|
| Network Frequency | 60 Hz |
| Number Of Input Connectors | 1 hard wire 5 wire (3P + N + E) |
| Input Current Limits | 200 A |

Output

| | |
|------------------|-------|
| Max Current Draw | 200 A |
|------------------|-------|

Conformance

| | |
|-----------|------------|
| Standards | UL 60950-1 |
|-----------|------------|

Environmental

| | |
|---------------------------------------|------------|
| Ambient Air Temperature For Operation | -5...40 °C |
|---------------------------------------|------------|

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

| | |
|-------------------------------------|------------------|
| Relative Humidity | 0...95 % |
| Operating Altitude | 0...10000 ft |
| Ambient Air Temperature For Storage | -25...65 °C |
| Storage Relative Humidity | 0...95 % |
| Storage Altitude | 0.00...3048.00 m |

Packing Units

| | |
|------------------|----------------|
| Package 1 Weight | 155 kg |
| Package 1 Height | 215 cm |
| Package 1 Width | 84.8 cm |
| Package 1 Length | 121 cm |
| Scc14 | 10731304296253 |

Contractual warranty

| | |
|----------|--------------------------|
| Warranty | 1 year repair or replace |
|----------|--------------------------|

Sustainability

Green Premium™ label label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. **Green Premium** promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low- products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

Eu Rohs Directive

Under investigation
