

Product data sheet

Specifications



APC Modular Power Distribution Unit, 266kVA, 400A, 480V:415V Auto-transformer, 72 Pole, 300mm

PDPM288G6H

Overview

Lead Time	Usually Ships within 6 Weeks
-----------	------------------------------

Main

Main Input Voltage	480 V 3 phases
Main Output Voltage	230 V 240 V
Other Output Voltage	240 V
Provided Equipment	Installation guide User manual

Physical

Height	199.1 cm
Width	29.8 cm
Depth	107.2 cm
Net Weight	522.73 kg
Mounting Location	Front
Mounting Preference	No preference
Mounting Mode	Not rack-mountable

Input

Network Frequency	60 Hz
Max Line Current	320 A
Load Capacity	266000 VA

Output

Max Current Draw	370 A
------------------	-------

Conformance

Product Certifications	UL listed
------------------------	-----------

Packing Units

Package 1 Weight	545.45 kg
Package 1 Height	213.4 cm
Package 1 Width	29.8 cm

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Package 1 Length	107.2 cm
------------------	----------

Contractual warranty

Warranty	1 year repair or replace
----------	--------------------------

Sustainability

Green Premium™ label label is Schneider Electric’s commitment to delivering products with best-in-class environmental performance. **Green Premium** promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low- products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

Eu Rohs Directive

Pro-active compliance (Product out of EU RoHS legal scope)

[EU RoHS Declaration](#)
