

Product data sheet

Specifications



Rack Distribution Panel 230 V

PDRDPH10U-R

⚠ Discontinued on: May 25, 2023

⚠ End-of-service on: Feb 21, 2024

⚠ Discontinued

Overview

Lead time Usually Ships within 3 Weeks

Main

Main Input Voltage 400 V 3 phases

Main Output Voltage 230 V
400 V 3 phases

Input Connection Type IEC 60309

Number of rack unit 42U

Number of cables 1

Provided equipment Installation guide
User manual

Physical

Colour Black

Height 207 cm

Width 61 cm

Depth 107.2 cm

net weight 272.74 kg

Mounting preference No preference

mounting mode Not rack-mountable

Input

Network frequency 50 Hz +/- 3 Hz

Input current limits 63 A

Load capacity 43000 VA

Conformance

Product certifications CE
VDE

Environmental

Ambient air temperature for operation 0...40 °C

Relative humidity 0...95 %

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Operating altitude	0...10000 ft
Ambient air temperature for storage	-15...45 °C
Storage Relative Humidity	0...95 %
Storage altitude	0.0000000000...9144.0000000000 m

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	226.1 cm
Package 1 Width	121.9 cm
Package 1 Length	91.4 cm
Package 1 Weight	295.46 kg

Contractual warranty

Warranty	1 year repair or replace
----------	--------------------------