

# Product data sheet

Specifications



## Personal SurgeArrest 3 Outlet 120V

PER3

⚠ Discontinued on: Jun 10, 2022

⚠ Discontinued

### Overview

Lead time Usually in Stock

### Main

Main Input Voltage 120 V

Input Connection Type NEMA 5-15P

Number of cables 1

Provided equipment User manual

### Physical

Colour Beige

Height 5.08 cm

Width 10.8 cm

Depth 15.88 cm

Net weight 0.36 kg

Mounting preference No preference

mounting mode Not rack-mountable

### Input

Maximum line current 15 A

Network frequency 50/60 Hz +/- 5 Hz manual switch

### Output

Number of power socket outlets 3

Outlet standard NEMA 5-15R

### Conformance

UL 1449 TVSS rating 330

Product certifications CSA

Standards UL 1283  
UL 1363  
UL 1449

Equipment protection policy Lifetime : \$50000

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

## Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-15...45 °C
Storage Relative Humidity	0...95 %
Storage altitude	0.0000000000...15240.0000000000 m

## Surge Protection and Filtering

EP joule rating	1060 J
Response time	0 ns common mode
Common mode rejection	60 dB
Peak current	13 kAcommon mode 6.5 kAnormal mode
Surge energy rate	240 J

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
SCC14	10731304000140

## Contractual warranty

Warranty	Limited Lifetime
----------	------------------