

Product data sheet

Specifications



APC Performance SurgeArrest 8 outlets with Phone, Coax & Network Protection 230V UK

PF8VNT3-UK

⚠ Discontinued on: Jul 16, 2021

⚠ Discontinued

Overview

Lead Time Usually in Stock

Main

Main Input Voltage	230 V
Input Connection Type	BS1363A British
Cable Length	3.05 m
Number Of Cables	1
Provided Equipment	2 x 1.8 m telephone cables 60 cm coaxial cable 6 ft network cable User manual

Physical

Colour	Charcoal
Height	37.2 cm
Width	12.2 cm
Depth	4.2 cm
Net Weight	1.23 kg
Mounting Preference	No preference
Mounting Mode	Not rack-mountable

Input

Maximum Line Current	13 A
Network Frequency	50/60 Hz

Output

Number Of Power Socket Outlets	8
Outlet Standard	BS 1363 United Kingdom

Conformance

Product Certifications	CE
Equipment Protection Policy	Lifetime : 100000 euros Lifetime : 75000 GBP

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Environmental

Ambient Air Temperature For Operation	0...40 °C
Relative Humidity	0...95 %
Operating Altitude	0...50000 ft
Ambient Air Temperature For Storage	-15...45 °C
Storage Relative Humidity	0...95 %
Storage Altitude	0.00...15240.00 m

Surge Protection and Filtering

Ep Joule Rating	3420 J
Data Line Protected	1-4 RJ11 / 3-6 RJ45
Response Time	0 ns common mode
Common Mode Rejection	70 dB
Peak Current	30 kA common mode 40 kA per phase normal mode
Surge Energy Rate	2525 J
Data Line Protection	RJ11 2-Way Modem/Fax/DSL splitter with protection (four wire dual lines) RJ45 10/100 Base-T Ethernet protection Cable modem/video protection

Packing Units

Package 1 Height	38.1 cm
Package 1 Width	21.6 cm
Package 1 Length	5.1 cm
Package 1 Weight	1.32 kg
Number Of Units In Package 2	12
Package 2 Length	685.80 mm
Package 2 Weight	15.88 kg
Number Of Units In Package 3	60
Scc14	10731304223679

Contractual warranty

Warranty	5 years (all other countries), Limited Lifetime (European Union countries only)
----------	---