Product data sheet Characteristics

PFMSB50042NA

SmartBunker FX 42U 8KVA UPS Air Cooled/DX In-RowRD - NAM



Overview

Model Name	SmartBunker FX 42U 8KVA UPS Air Cooled/DX In-RowRD - NAM	
Includes	User Manual	
Standard Lead Time	Special Order - Call for Quoted Lead Times	
Product Distribution	Aruba , Bahamas , Barbados , Belize , Bermuda , Brazil , Canada , Cayman Islands , Colombia , Costa Rica , Cuba , Dominica , Dominican Republic , Ecuador , El Salvador , Falkland Islands (Malvinas) , Guatemala , Guyana , Haiti , Honduras , Mexico , Nicaragua , Panama , Peru , Puerto Rico , Trinidad And Tobago , United States , Venezuela , VIRGIN ISLANDS (UNITED STATES)	

Batteries & Runtime

Battery Type	Maintenance-free sealed Lead-Acid battery with suspended electrolyte : leakproof	
Battery Volt-Amp-Hour Capacity	1728	<u></u>
Typical recharge time	1.5 hour(s)	
RBC Quantity	1	

Physical

Maximum Height	86.6 inches (2200.0 mm)	d for
Maximum Width	43.3 inches (1100.0 mm)	
Maximum Depth	59.05 inches (1500.0 mm)	<u>0</u>
Net Weight	1500.0 lbs (680.39 kg)	<u>۵</u> ي.
Shipping Weight	1850.0 lbs (839.15 kg)	9
Rack Height	42 U	ණ
Rack Free Space	38 U	bsd it

Environmental

Audible noise at 1 meter from surface	0.000 dB
of unit	