

PFMSB51042

SmartBunker FX 42U 5KVA UPS Air Cooled In-Row SC



PFMSB51042 has not been replaced. Please contact your customer care center for more information.

Overview

Model Name	SmartBunker FX 42U 5KVA UPS Air Cooled In-Row SC
Includes	Rack Mounting support rails , Rack Power Distribution Unit (PDU)
Standard Lead Time	Special Order - Call for Quoted Lead Times
Product Distribution	Albania , Algeria , Andorra , Angola , Anguilla , Antigua And Barbuda , Argentina , Austria , Azerbaijan , Bahrain , Belarus , Belgium , Benin , Bolivia , Bosnia And Herzegovina , Botswana , Brazil , Bulgaria , Burkina Faso , Burundi , Cameroon , Central African Republic , Chad , Chile , Congo , CONGO, THE DEMOCRATIC REPUBLIC OF THE , Cote D'Ivoire , Croatia , Cyprus , Czech Republic , Denmark , Djibouti , Egypt , Equatorial Guinea , Eritrea , Estonia , Ethiopia , Finland , France , Gabon , Gambia , Georgia , Germany , Ghana , Gibraltar , Greece , Grenada , Guadeloupe , Guinea , French Guiana , Hungary , Iceland , Iran (Islamic Republic Of) , Iraq , Ireland , Israel , Italy , Jamaica , Jordan , Kazakhstan , Kenya , Kuwait , Latvia , Lebanon , Lesotho , Liberia , Liechtenstein , Lithuania , Luxembourg , Macedonia , Madagascar , Malawi , Mali , Malta , Martinique , Mauritania , Mauritius , Mayotte , Moldova, Republic Of , Mongolia , Morocco , Mozambique , Namibia , Netherlands , Netherlands Antilles , Niger , Nigeria , Norway , Oman , Pakistan , Paraguay , Peru , Poland , Portugal , Qatar , Reunion , Romania , Russian Federation , Rwanda , SAINT KITTS AND NEVIS , SAINT LUCIA , SAINT VINCENT AND THE GRENADINES , Saudi Arabia , Senegal , Sierra Leone , Slovakia (Slovak Republic) , Slovenia , Somalia , South Africa , Spain , Sudan , Suriname , Sweden , Switzerland , Tajikistan , TANZANIA, UNITED REPUBLIC OF , Togo , Tunisia , Turkey , Turkmenistan , Turks And Caicos Islands , Uganda , Ukraine , United Arab Emirates , Uruguay , Uzbekistan , Western Sahara , Yemen , Zambia , Zimbabwe

Output

PDU Type	Basic
----------	-------

Input

Input Frequency	50 Hz
-----------------	-------

Batteries & Runtime

Battery Type	Maintenance-free sealed Lead-Acid battery with suspended electrolyte : leakproof
Battery Volt-Amp-Hour Capacity	1728
Typical recharge time	1.5 hour(s)
RBC Quantity	1

Physical

Maximum Width	1100.0 mm
Maximum Depth	1500.0 mm
Net Weight	680.39 kg
Shipping Weight	839.15 kg
Shipping Height	2200.0 mm
Rack Height	42 U
Rack Free Space	38 U
Number of Racks	1

Environmental

Audible noise at 1 meter from surface of unit	0.000 dB
---	----------