# Product data sheet

Specifications

## APC Performance SurgeArrest 8 outlets with Phone & Coax Protection 230V Russia

PMF83VT-RS

⚠ Discontinued on: Feb 14, 2024

⚠ **To be discontinued**

## Overview

| | |
|---|---|
| **Lead Time** | Usually in Stock |

## Main

| | |
|---|---|
| **Main Input Voltage** | 230 V |
| **Input Connection Type** | Schuko CEE 7/7P |
| **Cable Length** | 3.00 m |
| **Number Of Cables** | 1 |
| **Provided Equipment** | User manual |

## Physical

| | |
|---|---|
| **Colour** | White |
| **Height** | 6.2 cm |
| **Width** | 32.7 cm |
| **Depth** | 11 cm |
| **Net Weight** | 0.94 kg |
| **Mounting Preference** | No preference |
| **Mounting Mode** | Rack-mounted |

## Input

| | |
|---|---|
| **Input Power** | 2300 W |
| **Network Frequency** | 50 Hz +/- 5 Hz |
| **Maximum Input Current** | 10 A |
| **Switching Current Capacity** | 10 A |

## Output

| | |
|---|---|
| **Number Of Power Socket Outlets** | 8 |
| **Outlet Standard** | Schuko CEE 7 |

## Conformance

| | |
|---|---|
| **Product Certifications** | CE<br>EAC |

Life Is On | Schneider Electric

# Environmental

| | |
|---|---|
| **Ambient Air Temperature For Operation** | 0…40 °C |
| **Relative Humidity** | 0…95 % non-condensing |
| **Operating Altitude** | 0...50000 ft |
| **Ambient Air Temperature For Storage** | -15…45 °C |
| **Storage Relative Humidity** | 0…95 % |
| **Storage Altitude** | 0.00…15240.00 m |

# Surge Protection and Filtering

| | |
|---|---|
| **Response Time** | 1 ns common mode |
| **Common Mode Rejection** | 60 dB |
| **Peak Current** | 48 kAcommon mode<br>60 kA per phase normal mode |
| **Surge Energy Rate** | 2690 J |

# Packing Units

| | |
|---|---|
| **Unit Type Of Package 1** | PCE |
| **Number Of Units In Package 1** | 1 |
| **Package 1 Height** | 6.4 cm |
| **Package 1 Width** | 17 cm |
| **Package 1 Length** | 36.5 cm |
| **Package 1 Weight** | 1.08 kg |
| **Number Of Units In Package 2** | 6 |
| **Package 2 Height** | 381.00 mm |
| **Package 2 Width** | 203.20 mm |
| **Package 2 Length** | 355.60 mm |
| **Package 2 Weight** | 6.93 kg |
| **Number Of Units In Package 3** | 78 |
| **Scc14** | 10731304313202 |

# Contractual warranty

| | |
|---|---|
| **Warranty** | 2 years repair or replace |

Life Is On | **Schneider Electric**

# Sustainability

**Green Premium™ label** is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-$CO_2$ products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >

Transparency    RoHS/REACh

## Well-being performance

✓ Reach Free Of Svhc

✓ Mercury Free

✓ Rohs Exemption Information          Yes

## Certifications & Standards

| | |
|---|---|
| **Reach Regulation** | REACh Declaration |
| **Eu Rohs Directive** | Compliant with Exemptions |
| **Environmental Disclosure** | Product Environmental Profile |
| **Circularity Profile** | End of Life Information |