

AV Surge Protectors

APC Premium A/V Surge Protector, 11 outlet, phone line & 2 pairs of coax protection (all w/splitter)



Protection from damaging power transients

Includes: 6ft Gold Plated Coaxial Cable, 6ft High speed internet cable

PR11T3V5

DISCONTINUED : recommended replacement product [P8VNTG](#)

 [Email Technical Specifications](#) Printer Friendly

Product Category

- AV Surge Protectors
 - **AV Surge Protectors**
- AV Power Filters (1)
- AV Power Conditioners with Battery (1)
- AV Cables (1)

[+ More Images](#)

Technical Specifications

Documentation

Output	
Number of Outlets	11
Receptacle Style	NEMA 5-15R
Input	
Nominal Input Voltage	120V
Input Frequency	50/60 Hz
Input Connections	NEMA 5-15P
Maximum Line Current per phase	15A
Cord Length	3.05 meters
Surge Protection and Filtering	
Surge energy rating	1700 Joules
eP Joule Rating	3400
EMI/RFI Noise rejection (100 kHz to 10 MHz)	70 dB
Peak Current Normal Mode	20 kAmps
Peak Current Common Mode	60 kAmps
Data Line Protection	RJ-11 Modem/Fax/DSL protection (four wire dual line),Cable modem / Video protection
Data Lines Protected (multi-line only)	1-4
Let Through Voltage Rating	< 40
Physical	
Net Weight	1.42 KG
Maximum Height	311.00 mm
Maximum Width	146.00 mm
Maximum Depth	38.00 mm
Shipping Weight	1.60 KG
Shipping Height	356.00 mm
Shipping Width	248.00 mm
Shipping Depth	54.00 mm
Master Carton Units	12.00
Master Carton Dimensions (Length x Width x Height)	476 x 290 x 419 mm
Master Carton Weight	19.55 KG
SCC Codes	1073130419986 8
Color	Silver Satin
Environmental	
Operating Environment	0 - 40 °C
Operating Relative Humidity	0 - 95%
Operating Elevation	0-15000 meters
Storage Temperature	-5 - 45 °C
Storage Relative Humidity	0 - 95%
Storage Elevation	0-15000 meters
Conformance	
Regulatory Approvals	CSA,UL 1363,UL 1449
Standard Warranty	Lifetime
UL 1449 TVSS Rating	330V