

Product data sheet

Specifications



Performance SurgeArrest 7 Outlet w/Tel 120V

PRF7T

⚠ Discontinued on: Jun 10, 2022

⚠ Discontinued

Overview

Lead Time Usually in Stock

Main

Main Input Voltage	120 V
Input Connection Type	NEMA 5-15P
Number Of Cables	1
Provided Equipment	2 x 1.8 m telephone cables User manual

Physical

Colour	Beige
Height	5.08 cm
Width	10.8 cm
Depth	26.67 cm
Net Weight	0.95 kg
Mounting Preference	No preference
Mounting Mode	Not rack-mountable

Input

Maximum Line Current	15 A
Network Frequency	50/60 Hz +/- 5 Hz auto-sensing

Output

Number Of Power Socket Outlets	7
Outlet Standard	NEMA 5-15R

Conformance

UI 1449 Tvss Rating	330
Product Certifications	CSA
Standards	FCC part 68 UL 497A UL 1283 UL 1363 UL 1449

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Equipment Protection Policy	Lifetime : \$100000
-----------------------------	---------------------

Environmental

Ambient Air Temperature For Operation	0...40 °C
Relative Humidity	0...95 %
Operating Altitude	0...10000 ft
Ambient Air Temperature For Storage	-15...45 °C
Storage Relative Humidity	0...95 %
Storage Altitude	0.00...15240.00 m

Surge Protection and Filtering

Ep Joule Rating	3420 J
Response Time	0 ns common mode
Common Mode Rejection	70 dB
Peak Current	26 kAcommon mode 13 kAnormal mode
Surge Energy Rate	480 J

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Scc14	10731304000669

Contractual warranty

Warranty	Limited Lifetime
----------	------------------