

APC Professional SurgeArrest, 8 outlet, 2 pairs phone line protection

PRO8T2

! Discontinued on: Nov 16, 2023

(!) Discontinued

Overview

Lead time Usually in Stock

Main

Main Input Voltage	120 V
Input Connection Type	NEMA 5-15P
Cable length	1.8 m
Number of cables	1
Provided equipment	2 x 1.8 m telephone cables User manual

Physical

Colour	Beige
Height	4.4 cm
Width	20.3 cm
Depth	14.6 cm
Net weight	1.06 kg
Mounting preference	No preference
Mounting mode	Not rack-mountable

Input

Network frequency 50/60 Hz +/- 5 Hz auto-sensing

Output

Number of power socket outlets	8
Outlet standard	NEMA 5-15R

Conformance

UL 1449 TVSS rating	330
Product certifications	CSA
Standards	UL 497B UL 1283 UL 1363 UL 1449

Equipment protection policy Lifetime: \$75000

Environmental

Ambient air temperature for operation	045 °C
Relative humidity	095 %
Operating altitude	010000 ft
Ambient air temperature for storage	-1545 °C
Storage Relative Humidity	095 %
Storage altitude	0.000000000015240.000000000 m

Surge Protection and Filtering

EP joule rating	1760 J
Data line protected	1-4
Response time	0 ns common mode
Common mode rejection	60 dB
Peak current	13 kAcommon mode 13 kAnormal mode
Surge energy rate	1120 J

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.1 cm
Package 1 Width	15.9 cm
Package 1 Length	31.8 cm
Package 1 Weight	1.14 kg
Number of Units in Package 2	12
Package 2 Weight	14.5 kg
Number of Units in Package 3	240
SCC14	10731304000836

Contractual warranty

Warranty Limited Lifetime

Sustainability

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



RoHS/REACh

Well-being performance

⊘	Reach Free Of Svhc	
②	Mercury Free	
⊘	Rohs Exemption Information	Yes

Certifications & Standards

Eu Rohs Directive	Compliant with Exemptions
Circularity Profile	End of Life Information